

MECHANICAL SYMBOLS LIST

AC-1	TXF-1	EQUIPMENT SYMBOL
AIR DEVICES		
		CEILING DIFFUSER SUPPLY
DUCT ACCESSORIES		
		BACK DRAFT DAMPER
		VOLUME DAMPER W/ ACCESS DOOR
		MOTORIZED DAMPER W/ ACCESS DOOR
CONTROLS AND SENSORS		
		THERMOSTAT
		TEMPERATURE SENSOR
DUCTWORK		
		AIR DUCT W/ 1.5" ACOUSTICAL LINING
		FLEXIBLE DUCT
		FLEXIBLE CONNECTION
		RECTANGULAR DUCT (WIDTH X DEPTH)
		ROUND DUCT (DIAMETER)
		ROUND DUCT CROSS SECTION
		SUPPLY AIR RECTANGULAR DUCT CROSS SECTION
		RETURN AIR RECTANGULAR DUCT CROSS SECTION

MECHANICAL ABBREVIATIONS

AL	ACOUSTIC LINING
AHU	AIR HANDLING UNIT
BDD	BACKDRAFT DAMPER
CDS	CEILING DIFFUSER SUPPLY
CDR	CEILING DIFFUSER RETURN
CFM	CUBIC FEET OF AIR PER MINUTE
CD	CONDENSATE DRAIN PIPE
CU	CONDENSER UNIT
DN	DOWN
EER	ENERGY EFFICIENCY RATIO
FC	FLEXIBLE CONNECTION
FD	FIRE DAMPER W/FUSIBLE LINK
HSPF	HEATING SEASONAL PERFORMANCE FACTOR
HWHT	HOT WATER HEATER
IEER	INTEGRATED ENERGY EFFICIENCY RATIO
OAI	OUTSIDE AIR INTAKE
SEER	SEASONAL ENERGY EFFICIENCY RATIO
TEF	TOILET EXHAUST FAN
UH	UNIT HEATER
VD	VOLUME DAMPER

MECHANICAL DRAWING LIST

MO.1	MECHANICAL GENERAL NOTES, SYMBOLS LIST & ABBREVIATIONS
MO.2	MECHANICAL SPECIFICATIONS
M1.1	MECHANICAL FLOOR AND ROOF PLANS
M5.1	MECHANICAL DETAILS
M6.1	MECHANICAL SCHEDULE

APPLICABLE CODE BERKELEY COUNTY, WV

- 2015 BUILDING CODE OF WEST VIRGINIA (IBC2015).
- ASHRAE STANDARD 90.1-2010 ENERGY CODE.
- INTERNATIONAL MECHANICAL CODE 2015.

INWOOD BERKELEY COUNTY BUILDING DEPARTMENT NOTES

ALL WORK SHALL COMPLY WITH APPLICABLE SECTIONS OF 2015 INTERNATIONAL BUILDING CODES AND ALL AMENDMENTS AND RULES AND REGULATIONS OF THE DEPARTMENT OF BUILDINGS TO DATE.

- THE CONTRACTOR SHALL ENGAGE THE SERVICES OF A PROFESSIONAL ENGINEER TO PROVIDE THE REQUIRED SPECIAL INSPECTIONS AND TESTS.
- TESTS WILL BE CONDUCTED UNDER DIRECTION OF A LICENSED PROFESSIONAL ENGINEER, ARCHITECT OR OTHER PERSON HAVING NOT LESS THAN FIVE (5) YEARS EXPERIENCE SUPERVISING THE INSTALLATION OF SUCH MECHANICAL SYSTEMS. THE TESTS WILL SHOW COMPLIANCE WITH 2015 INTERNATIONAL BUILDING CODE REQUIREMENTS AS OUTLINES IN SECTION [BC 1704].
- THE LICENSED PROFESSIONAL ENGINEER, ARCHITECT OR OTHER PERSON HAVING NOT LESS THAN FIVE (5) YEARS EXPERIENCE SUPERVISING THE INSTALLATION OF SUCH MECHANICAL SYSTEMS AND CONDUCTING SUCH TESTS WILL FILE DOCUMENTATION AND REPORTS OF TESTS THAT THE SYSTEM COMPLIES WITH THE CONSTRUCTION DOCUMENTS AND APPLICABLE LAWS.
- TESTS OF MECHANICAL SYSTEMS SHALL BE PERFORMED IN ACCORDANCE WITH SECTION MC 113 AND THE FOLLOWING SECTIONS OF THE 2015 INTERNATIONAL MECHANICAL CODE:
 - VENTILATION SYSTEM BALANCING MC 403.3.1.5
- THE FOLLOWING WORK ITEMS, COMPONENTS, MATERIALS, CAPACITIES, ETC. SHALL COMPLY WITH THE REFERENCED CODE OR STANDARD:
 - DUCT CONSTRUCTION AND INSTALLATION- MC 603
 - AIR FILTERS - MC 605
- INTERIOR SPACES INTENDED FOR HUMAN OCCUPANCY SHALL BE PROVIDED WITH ACTIVE OR PASSIVE SPACE HEATING SYSTEMS CAPABLE OF MAINTAINING AN INDOOR TEMPERATURE OF NOT LESS THAN 68°F AT A POINT 3 FEET ABOVE THE FLOOR ON THE DESIGN HEATING DAY.
- VENTILATION FOR ALL AREA SHALL COMPLY WITH MC 401.
- A STATEMENT SHALL BE FILED BY THE OWNER OR TENANT IN POSSESSION THAT THE VENTILATION SYSTEM WILL BE KEPT IN CONTINUOUS OPERATION AT ALL TIMES DURING THE NORMAL OCCUPANCY OF THE STRUCTURE AS REQUIRED BY MC 403.3
- REFER TO ARCHITECTURAL DRAWINGS FOR REQUIRED FIRE-RATED WALL AND SMOKE WALL CONSTRUCTION AND LOCATION.
- THESE PLANS ARE APPROVED ONLY FOR THE WORK INDICATED ON THE APPLICATION SPECIFICATION SHEET. ALL OTHER MATTERS SHOWN ARE NOT TO BE RELIED UPON OR TO BE CONSIDERED AS EITHER BEING APPROVED OR IN ACCORDANCE WITH APPLICABLE CODES.
- MECHANICAL SYSTEMS SHALL BE COMMISSIONED PER ASHRAE STANDARD 90.1-2010 6.7.2.4 FINAL COMMISSIONING REPORT SHALL BE DUE WITHIN 90 DAYS OF RECEIPT OF CERTIFICATE OF OCCUPANCY.
- A COMMISSIONING PLAN SHALL BE DEVELOPED BY A LICENSED DESIGN PROFESSIONAL, MECHANICAL ENGINEER OR APPROVED AGENCY.
- A WRITTEN REPORT DESCRIBING THE ACTIVITIES AND MEASUREMENTS COMPLETED IN ACCORDANCE WITH SECTION ASHRAE STANDARD 90.1-2010, 6.7.2.3.
- ALL HEATING AND COOLING LOADS CALCULATED PER ASHRAE/ACCA 183.

GENERAL NOTES

- CONTRACTOR SHALL SURVEY THE AREA OF THIS WORK BEFORE SUBMITTING A BID AND SHALL BE RESPONSIBLE FOR NOTIFYING THE ARCHITECT OF ANY CONDITIONS WHICH WOULD PREVENT THE INSTALLATION OF THE WORK AS SHOWN ON DRAWINGS.
- ALL APPLICABLE CODES, LAWS AND REGULATIONS GOVERNING OR RELATING TO ANY PORTION OF THIS WORK ARE HEREBY INCORPORATED INTO AND MADE A PART OF THESE SPECIFICATIONS, AND THEIR PROVISIONS SHALL BE CARRIED OUT BY THE CONTRACTOR WHO SHALL INFORM THE OWNER, PRIOR TO SUBMITTING A PROPOSAL, OF ANY WORK OR MATERIALS WHICH VIOLATE ANY OF THE ABOVE LAWS AND REGULATIONS. ANY WORK DONE BY THE CONTRACTOR CAUSING SUCH VIOLATION SHALL BE CORRECTED BY THE CONTRACTOR.
- BEFORE PROCEEDING WITH ANY WORK IN OCCUPIED OR USED AREAS, THE CONTRACTOR SHALL APPLY TO OWNER FOR PERMISSION TO ENTER SUCH AREAS. THE CONTRACTOR IS OBLIGED TO PERFORM HIS WORK ONLY AT THE TIMES DESIGNATED BY OWNER. THERE WILL BE NO ADDITIONAL COMPENSATION FOR THE WORK PERFORMED AFTER HOURS OR ON OFF-DAYS WITHOUT PRIOR WRITTEN APPROVAL.
- THE WORK IN THE BUILDING SHALL BE DONE WHEN AND AS DIRECTED, AND IN A MANNER SATISFACTORY TO THE OWNER. THE WORK SHALL BE PERFORMED SO AS TO CAUSE THE LEAST POSSIBLE INCONVENIENCE AND DISTURBANCE TO THE PRESENT OCCUPANTS.
- THE CONTRACTOR'S PROPOSAL FOR ALL WORK SHALL BE PREDICATED ON THE PERFORMANCE OF THE WORK DURING REGULAR WORKING HOURS. WHEN SO DIRECTED, HOWEVER, THE CONTRACTOR SHALL INSTALL WORK IN OVERTIME AND THE ADDITIONAL COST TO BE CHARGED THEREFORE SHALL BE ONLY THE "PREMIUM" PORTION OF THE WAGES PAID.
- CONTRACTOR SHALL ASCERTAIN THE APPROPRIATE METHOD FOR BRINGING THE UNITS INTO AND THROUGH THE BUILDING TO POSITION UNIT IN LOCATION SHOWN ON THE PLANS, WHERE NECESSARY, EQUIPMENT SHALL BE SHIPPED FROM MANUFACTURER IN SECTIONS OF SIZE SUITABLE FOR MOVING THROUGH RESTRICTIVE SPACES. COORDINATE WITH BUILDING OWNER APPROPRIATE TIMES OF DAY SUCH EQUIPMENT MAY BE MOVED THROUGH ALL AREAS.
- DUCTWORK AND PIPING IS SHOWN DIAGRAMMATICALLY AND DOES NOT SHOW ALL OFFSETS, DROPS AND RISES OF RUNS. THE CONTRACTOR SHALL MAKE ALLOWANCE IN PRICING FOR ROUTING OF DUCTWORK AND PIPING TO AVOID OBSTRUCTIONS. EXACT LOCATIONS ARE SUBJECT TO APPROVAL OF ARCHITECT. COORDINATION WITH THE EXISTING SERVICES, INCLUDING THOSE OF OTHER TRADES IS REQUIRED.

- REMOVAL AND RELOCATION OF CERTAIN EXISTING WORK WILL BE NECESSARY FOR THE PERFORMANCE OF THE GENERAL WORK. ALL EXISTING CONDITIONS CANNOT BE COMPLETELY DETAILED ON THE DRAWINGS. THE CONTRACTOR SHALL SURVEY THE SITE AND INCLUDE ALL CHANGES IN MAKING UP THE WORK PROPOSAL.
- DISCONNECT, REMOVE AND/OR RELOCATE EXISTING MATERIAL, EQUIPMENT AND OTHER WORK AS NOTED OR REQUIRED FOR PROPER INSTALLATION OF NEW SYSTEM.
- CONNECT NEW WORK TO EXISTING WORK IN NEAT AND APPROVED MANNER. RESTORE EXISTING WORK DISTURBED WHILE INSTALLING NEW WORK TO ACCEPTABLE CONDITION AS DETERMINED BY ARCHITECT.
- PLAN INSTALLATION OF NEW WORK AND CONNECTIONS TO EXISTING WORK TO INSURE MINIMUM INTERFERENCE WITH REGULAR OPERATION OF EXISTING FACILITIES. ALL SYSTEM SHUTDOWNS AFFECTING OTHER AREAS SHALL BE COORDINATED WITH BUILDING OWNER. INSTALL ISOLATION VALVES AT POINT OF CONNECTION TO THE EXISTING PIPING. PROVIDE TEMPORARY DUCT CAPS AND/OR CONNECTIONS TO MINIMIZE SHUTDOWN TIME.
- SUPPORT ALL DUCTWORK AND PIPING FROM BUILDING STRUCTURE AND/OR FRAMING IN AN APPROVED MANNER. WHERE OVERHEAD CONSTRUCTION DOES NOT PERMIT FASTENING OR SUPPORTS FOR EQUIPMENT, FURNISH ADDITIONAL FRAMING. INSERTS SHALL BE STEEL, SLOTTED TYPE AND FACTORY PAINTED. SINGLE ROD SHALL BE SIMILAR TO GRINNELL FIG. 251. MULTI-ROD SHALL BE SIMILAR TO FEE & MASON SERIES 9000 WITH END CAPS AND CLOSURE STRIPS. MAXIMUM LOADING INCLUDING PIPES, DUCTWORK CONTENTS AND COVERING SHALL NOT EXCEED 75% OF RATED INSERT CAPABILITY. WHEN SUPPORTING FROM BUILDING USE BEAM CLAMPS IN APPROVED MANNER.
- PROVIDE ALL NECESSARY FLASHING AND COUNTER FLASHING TO MAINTAIN THE WATERPROOFING INTEGRITY OF THIS BUILDING AS REQUIRED BY THE INSTALLATION OR REMOVAL OF PIPES, DUCTS, LOUVERS, CONDUIT, AND EQUIPMENT. PROVIDE EQUIPMENT CURBS AND DUNNAGE STEEL AS REQUIRED.
- SEAL OPENINGS AROUND DUCTS AND PIPING THROUGH PARTITIONS, WALLS AND FLOORS (NOT IN SHAFTS) WITH MINERAL WOOL OR OTHER NONCOMBUSTIBLE MATERIAL (FIBERGLASS INSULATION IS NOT ACCEPTABLE).
- WHERE PENETRATIONS THROUGH FIRE RATED WALLS ARE NOT FIRE PROOFED THIS CONTRACTOR SHALL BE RESPONSIBLE TO SEAL SAME TO MAINTAIN THE RATED INTEGRITY.
- INSTALL WORK SO AS TO BE READILY ACCESSIBLE FOR OPERATION, MAINTENANCE AND REPAIR. MINOR DEVIATIONS FROM DRAWINGS MAY BE MADE TO ACCOMPLISH THIS, BUT CHANGES WHICH INVOLVE EXTRA COST SHALL NOT BE MADE WITHOUT APPROVAL.
- ACCESS DOORS ARE REQUIRED FOR ALL BUILDING SERVICE VALVES THAT RUN THROUGH THE SPACE, AND ACCESS DOOR SHALL HAVE THE EQUAL RATED CAPACITY (1HR, 2HR, ETC.) AS WALL. COORDINATE ALL LOCATIONS OF ACCESS DOORS WITH THE ARCHITECT.
- REMOVABLE ACCESS TILE AND/OR ACCESS DOOR ARE REQUIRED IN HUNG CEILINGS, SHAFTS AND WALLS FOR ALL VOLUME AND FIRE DAMPERS, AUTOMATIC DAMPERS AND ALL OTHER MECHANICAL EQUIPMENT AND DEVICES. VAC CONTRACTOR TO FURNISH ACCESS LOCATION REQUIREMENTS TO GENERAL CONTRACTOR. ACCESS TILE IDENTIFICATION: PROVIDE BUTTONS, TABS, AND MARKERS TO IDENTIFY LOCATION OF CONCEALED VALVES, DAMPERS AND EQUIPMENT.
- THE CONTRACTOR SHALL KEEP ALL EQUIPMENT AND MATERIALS, AND ALL PARTS OF THE BUILDING, EXTERIOR SPACES AND ADJACENT STREETS, SIDEWALKS AND PAVEMENTS, FREE FROM MATERIAL AND DEBRIS RESULTING FROM THE EXECUTION OF THIS WORK. EXCESS MATERIALS WILL NOT BE PERMITTED TO ACCUMULATE EITHER ON THE INTERIOR OR THE EXTERIOR.
- UNLESS OTHERWISE SPECIFICALLY SPECIFIED, INCLUDE ALL CUTTING AND PATCHING OF EXISTING FLOORS, WALLS, PARTITIONS AND OTHER MATERIALS IN THE EXISTING BUILDING. THE CONTRACTOR SHALL RESTORE THESE AREAS TO ORIGINAL CONDITION.
- MATERIALS AND WORKMANSHIP, UNLESS OTHERWISE NOTED, SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.
- ALL EQUIPMENT SHALL BE PROVIDED WITH ONE YEAR WARRANTY PARTS AND LABOR AND FIVE YEARS ON COMPRESSORS. WARRANTY PERIOD BEGINS UPON PROJECT ACCEPTANCE
- ALL MATERIAL AND EQUIPMENT TO BE NEW UNLESS OTHERWISE NOTED AND SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR HIS WORK WITH ITS COMPLETION AND FINAL ACCEPTANCE AND SHALL REPLACE ANY OF THE SAME WHICH MAY BE DAMAGED, LOST, OR STOLEN WITHOUT ADDITIONAL COST TO THE OWNER.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE FAILURE OF ANY DUCTWORK SYSTEM OR EQUIPMENT TO FUNCTION PROPERLY UPON COMPLETION OF HIS WORK UPON SAID SYSTEM OR EQUIPMENT.
- SUBMIT SHOP DRAWING OF ALL WORK WHICH MUST BE APPROVED BY THE ARCHITECT AND ENGINEER BEFORE WORK COMMENCES.
- SUBMISSION OF A PROPOSAL SHALL BE CONSTRUED AS EVIDENCE THAT A CAREFUL EXAMINATION OF THE PORTIONS OF THE EXISTING BUILDING, EQUIPMENT, ETC., WHICH AFFECT THIS WORK, AND THE ACCESS TO SUCH SPACES, HAS BEEN MADE AND THAT THE CONTRACTOR IS FAMILIAR WITH EXISTING CONDITIONS AND DIFFICULTIES THAT WILL AFFECT THE EXECUTION OF THE WORK. LATER CLAIMS SHALL NOT BE MADE FOR LABOR, EQUIPMENT OR MATERIALS REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WHICH COULD HAVE BEEN FORESEEN DURING SUCH AN EXAMINATION. THE ON-SITE INSPECTION SHALL VERIFY EXISTING DUCTWORK, PIPING (SIZES, CLEARANCES, ETC) AND CONDITIONS.
- INSURANCE: IN ACCORDANCE WITH BUILDING REQUIREMENTS THE CONTRACTOR SHALL INCLUDE A HOLD HARMLESS CLAUSE FOR OWNER AND ENGINEER.
- THE FINAL ACCEPTANCE WILL BE MADE AFTER THE CONTRACTOR HAS ADJUSTED HIS EQUIPMENT, BALANCED THE VARIOUS SYSTEMS, DEMONSTRATED THAT IT FULFILLS THE REQUIREMENTS OF THE DRAWINGS AND SPECIFICATIONS AND HAS FURNISHED ALL THE REQUIRED CERTIFICATES OF INSPECTION AND APPROVAL.

- SPECIFICATIONS ARE OF SIMPLIFIED FORM AND INCLUDE INCOMPLETE SENTENCES, WORDS OR PHRASES SUCH AS "THE CONTRACTOR SHALL," "SHALL BE," "FURNISH," "PROVIDE," "A," "THE," AND "ALL" HAVE BEEN OMITTED FOR BREVITY.
 - WHERE A CONFLICT EXISTS BETWEEN THE DRAWINGS, THE SPECIFICATIONS OR ANY OTHER CONSTRUCTION DOCUMENT, THE ONE WITH THE MOST STRINGENT REQUIREMENT(S) SHALL APPLY.
- DEFINITIONS:
- "PROVIDE": TO SUPPLY, INSTALL AND CONNECT UP COMPLETE AND READY FOR SAFE AND REGULAR OPERATION THE PARTICULAR WORK REFERRED TO UNLESS SPECIFICALLY OTHERWISE NOTED.
 - "INSTALL": TO ERECT, MOUNT AND CONNECT COMPLETE WITH RELATED ACCESSORIES.
 - "FURNISH" OR "SUPPLY": TO PURCHASE, PROCURE, ACQUIRE AND DELIVER COMPLETE WITH RELATED ACCESSORIES.

SCOPE OF WORK

- THE WORK UNDER CONTRACT INCLUDES ALL LABOR, MATERIALS AND APPLIANCES NECESSARY FOR THE FURNISHING, INSTALLING AND TESTING, COMPLETE AND READY FOR SAFE OPERATION OF THE SYSTEMS AS DESCRIBED IN THE SPECIFICATIONS, FLOOR PLANS(S) DESIGN, DETAIL DRAWINGS, NOTES, RIS, ETC. FOR THIS PROJECT. WORK SHALL BE INSTALLED IN A NEAT, WORKMANLIKE MANNER.
- THE CONTRACTOR SHALL GIVE NECESSARY NOTICE, FILE DRAWINGS AND SPECIFICATIONS WITH THE DEPARTMENT HAVING JURISDICTION, OBTAIN PERMITS OR LICENSES NECESSARY TO CARRY OUT THIS WORK AND PAY ALL FEES THEREFOR. THE CONTRACTOR SHALL ARRANGE FOR INSPECTION AND TESTS OF ANY OR ALL PARTS OF THE WORK IF SO REQUIRED BY AUTHORITIES AND PAY ALL CHARGES FOR SAME. THE CONTRACTOR SHALL PAY ALL COSTS FOR, AND FURNISH TO THE OWNER BEFORE FINAL BILLING, ALL CERTIFICATES NECESSARY AS EVIDENCE THAT THE WORK INSTALLED CONFORMS WITH ALL REGULATIONS WHERE THEY APPLY TO THIS WORK.
- THE CONTRACTOR SHALL FURNISH A WRITTEN GUARANTEE TO REPLACE OR REPAIR PROMPTLY AND ASSUME RESPONSIBILITY FOR ALL EXPENSES INCURRED FOR ANY WORKMANSHIP AND EQUIPMENT IN WHICH DEFECTS DEVELOP WITHIN ONE YEAR FROM THE DATE OF FINAL CERTIFICATE FOR PAYMENT AND/OR FROM DATE OF ACTUAL USE OF EQUIPMENT OR OCCUPANCY OF SPACES; BY OWNER, INCLUDED UNDER THE VARIOUS PARTS OF THE WORK, WHICHEVER DATE IS EARLIER. THIS WORK SHALL BE DONE AS DIRECTED BY THE OWNER. THIS GUARANTEE SHALL ALSO PROVIDE THAT WHERE DEFECTS OCCUR, THE CONTRACTOR WILL ASSUME RESPONSIBILITY FOR ALL EXPENSES INCURRED IN REPAIRING AND REPLACING WORK OF OTHER TRADES AFFECTED BY DEFECTS, REPAIRS OR REPLACEMENTS IN EQUIPMENT SUPPLIED BY THE CONTRACTOR.

GENERAL HVAC NOTES

GENERAL:

- PROVIDE ALL MATERIAL AND EQUIPMENT AND PERFORM ALL LABOR REQUIRED TO INSTALL COMPLETE AND OPERABLE MECHANICAL SYSTEMS AS INDICATED ON THE DRAWINGS, AS SPECIFIED AND AS REQUIRED BY CODE.
- CONTRACT DOCUMENT DRAWINGS FOR MECHANICAL WORK (HVAC, PLUMBING, AND FIRE PROTECTION) ARE DIAGRAMMATIC AND ARE INTENDED TO CONVEY SCOPE AND GENERAL ARRANGEMENT ONLY.
- THE LOCATIONS OF ALL ITEMS SHOWN ON THE DRAWINGS OR CALLED FOR IN THE SPECIFICATIONS THAT ARE NOT FIXED BY DIMENSIONS ARE APPROXIMATE ONLY. THE EXACT LOCATIONS NECESSARY TO SECURE THE BEST CONDITIONS AND RESULTS MUST BE DETERMINED BY THE PROJECT SITE CONDITIONS AND SHALL HAVE THE APPROVAL OF THE ENGINEER BEFORE BEING INSTALLED. DO NOT SCALE DRAWINGS.
- WHEN MECHANICAL WORK (HVAC, PLUMBING, SHEET METAL, FIRE PROTECTION, ETC.) IS SUBCONTRACTED, IT SHALL BE THE MECHANICAL CONTRACTOR'S RESPONSIBILITY TO COORDINATE SUBCONTRACTORS AND THE ASSOCIATED CONTRACTS. WHEN DISCREPANCIES ARISE PERTAINING TO WHICH CONTRACTOR PROVIDES A PARTICULAR ITEM OF THE MECHANICAL CONTRACT OR WHICH CONTRACTOR PROVIDES FINAL CONNECTIONS FOR A PARTICULAR ITEM OF THE MECHANICAL CONTRACT, IT SHALL BE BROUGHT TO THE ATTENTION OF THE MECHANICAL CONTRACTOR, WHOSE DECISION SHALL BE FINAL.
- COORDINATE CONSTRUCTION OF ALL MECHANICAL WORK WITH ARCHITECTURAL, STRUCTURAL, CIVIL, ELECTRICAL WORK, ETC., SHOWN ON OTHER CONTRACT DOCUMENT DRAWINGS.
- INSTALL ALL MECHANICAL EQUIPMENT AND APPURTENANCES IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS, CONTRACT DOCUMENTS, AND APPLICABLE CODES AND REGULATIONS.
- WHERE TWO OR MORE ITEMS OF THE SAME TYPE OF EQUIPMENT ARE REQUIRED, THE PRODUCT OF ONE MANUFACTURER SHALL BE USED.
- COORDINATE ALL EQUIPMENT CONNECTIONS WITH MANUFACTURERS' CERTIFIED DRAWINGS. COORDINATE AND PROVIDE ALL DUCT AND PIPING TRANSITIONS REQUIRED FOR FINAL EQUIPMENT CONNECTIONS TO FURNISHED EQUIPMENT. FIELD VERIFY AND COORDINATE ALL DUCT AND PIPING DIMENSIONS BEFORE FABRICATION.
- ALL CONTROL WIRE AND CONDUIT SHALL COMPLY WITH THE NATIONAL ELECTRIC CODE AND ELECTRICAL DIVISION OF THE SPECIFICATION.
- ALL CONTROL WIRE AND CONDUIT SHALL COMPLY WITH THE NATIONAL ELECTRIC CODE AND ELECTRICAL DIVISION OF THE SPECIFICATION.
- PROVIDE VIBRATION ISOLATION FOR ALL MECHANICAL EQUIPMENT TO PREVENT TRANSMISSION OF VIBRATION TO BUILDING STRUCTURE.
- LOCATE ALL TEMPERATURE, PRESSURE, AND FLOW MEASURING DEVICES IN ACCESSIBLE LOCATIONS WITH THE STRAIGHT SECTION OF PIPE OR DUCT UP- AND DOWNSTREAM AS RECOMMENDED BY THE MANUFACTURER FOR GOOD ACCURACY.
- ALL MISCELLANEOUS STEEL REQUIRED TO ENSURE PROPER INSTALLATION AND AS SHOWN IN THE DETAILS FOR PIPING, DUCTWORK, AND EQUIPMENT (UNLESS OTHERWISE NOTED) SHALL BE FURNISHED AND INSTALLED BY THE MECHANICAL CONTRACTOR.
- PROVIDE ACCESS PANELS FOR INSTALLATION IN WALLS AND CEILINGS, WHERE REQUIRED, TO SERVICE DAMPERS, VALVES,

- SMOKE DETECTORS, AND OTHER CONCEALED MECHANICAL EQUIPMENT. ACCESS PANELS SHALL BE TURNED OVER TO THE GENERAL CONTRACTOR FOR INSTALLATION. ACCESS PANELS SHALL HAVE THE EQUAL RATED CAPACITY (1HR, 2HR, ETC.) AS WALL.
 - MECHANICAL EQUIPMENT, DUCTWORK, AND PIPING SHALL NOT BE SUPPORTED FROM A METAL DECK.
 - ALL EQUIPMENT, PIPING, DUCTWORK, ETC., SHALL BE SUPPORTED AS DETAILED, SPECIFIED AND REQUIRED TO PROVIDE A VIBRATION-FREE INSTALLATION.
 - ALL DUCTWORK, PIPING, AND EQUIPMENT SUPPORTED FROM STRUCTURAL STEEL SHALL BE COORDINATED WITH THE GENERAL CONTRACTOR. ALL ATTACHMENTS TO STEEL BAR JOISTS, TRUSSES OR JOIST GIRDERS SHALL BE AT PANEL POINTS. PROVIDE BEAM CLAMPS MEETING MSS STANDARDS. WELDING TO STRUCTURAL MEMBERS SHALL NOT BE PERMITTED. THE USE OF C-CLAMPS SHALL NOT BE PERMITTED.
 - ALL ROOF-MOUNTED EQUIPMENT CURBS FOR EQUIPMENT PROVIDED BY THE MECHANICAL CONTRACTOR SHALL BE FURNISHED BY THE MECHANICAL CONTRACTOR AND INSTALLED BY THE GENERAL CONTRACTOR.
 - LOCATIONS AND SIZES OF ALL FLOOR, WALL, AND ROOF OPENINGS SHALL BE COORDINATED WITH ALL OTHER TRADES INVOLVED.
 - ALL OPENINGS IN FIRE WALLS DUE TO DUCTWORK, PIPING, CONDUIT, ETC., SHALL BE FIRE STOPPED WITH A PRODUCT SIMILAR TO 3M OR APPROVED EQUAL.
 - ALL AIR CONDITIONING CONDENSATE DRAIN LINES FROM EACH ROOFTOP UNIT SHALL BE PIPED FULL SIZE OF THE UNIT DRAIN OUTLET, WITH "P" TRAP, AND PIPED TO THE NEAREST DRAIN. SEE THE DETAILS SHOWN IN THE DRAWINGS OR THE CONTRACT SPECIFICATIONS FOR THE DEPTH OF THE AIR CONDITIONING CONDENSATE TRAP.
 - REFER TO TYPICAL DETAILS FOR DUCTWORK, PIPING, AND EQUIPMENT INSTALLATION.
 - REINFORCEMENT, DETAILING, AND PLACEMENT OF CONCRETE SHALL CONFORM TO ASTM 315 AND ACI 318. CONCRETE SHALL CONFORM TO ASTM C94. CONCRETE WORK SHALL CONFORM TO ACI 318 PART ENTITLED "CONSTRUCTION REQUIREMENTS". COMPRESSIVE STRENGTH IN 28 DAYS SHALL BE 3,000 PSI. TOTAL AIR CONTENT OR EXTERIOR CONCRETE SHALL BE BETWEEN 5 AND 7 PERCENT BY VOLUME. SLUMP SHALL BE BETWEEN 3 AND 4 IN. CONCRETE SHALL BE CURED FOR 7 DAY AFTER PLACEMENT.
 - ALL TESTS SHALL BE COMPLETED BEFORE ANY MECHANICAL EQUIPMENT OR PIPING INSULATION IS APPLIED.
 - TESTING, ADJUSTING, AND BALANCING AGENCY SHALL BE A MEMBER OF THE ASSOCIATED AIR BALANCE COUNCIL (AABC) OR THE NATIONAL ENVIRONMENTAL BALANCING BUREAU (NEBB). TESTING, ADJUSTING, AND BALANCING SHALL BE PERFORMED IN ACCORDANCE WITH THE AABC STANDARDS.
- HVAC DUCTWORK - SHEET METAL
- CERTAIN ITEMS SUCH AS RISES AND DROPS IN DUCTWORK, ACCESS DOORS, VOLUME DAMPERS, ETC., ARE INDICATED ON THE CONTRACT DOCUMENT DRAWINGS FOR CLARITY FOR A SPECIFIC LOCATION REQUIREMENT AND SHALL NOT BE INTERPRETED AS THE EXTENT OF THE REQUIREMENTS FOR THESE ITEMS.
 - CONTRACTOR TO CHECK AND CORRECT ANY AND ALL DEFICIENCIES IN EXISTING DUCTS. ALL NEW DUCTWORK WILL COMPLY WITH THE LATEST SMACNA GUIDELINES AND CONFORM WITH REQUIREMENTS OF THE LATEST HANDBOOKS PUBLISHED BY ASHRAE.
 - PROVIDE VOLUME DAMPER AT EACH TAP TO MAIN DUCT AND WHERE NECESSARY TO PROPERLY BALANCE SYSTEM.
 - SUPPLY AND RETURN DUCTWORK 20' FROM ALL AC UNITS SHALL BE LINED WITH 1.5" ACOUSTICAL LINING.
 - CONTRACTOR SHALL SUPPLY AND INSTALL ALL NECESSARY SUPPLY DIFFUSERS AND RETURN AIR REGISTERS WHERE INDICATED ON THE DRAWING. COORDINATE LOCATION OF DIFFUSERS AND REGISTERS WITH REFLECTED CEILING PLAN.
 - IN CORRIDORS WHERE CEILING SPEAKERS AND AIR DIFFUSERS ARE INDICATED BETWEEN THE SAME LIGHT FIXTURES, INSTALL BOTH DEVICES AT THE QUARTER POINTS BETWEEN THE FIXTURES.
 - UNLESS OTHERWISE SHOWN, LOCATE ALL ROOM THERMOSTATS AND HUMIDISTAT 4'-0" (CENTER LINE) ABOVE THE FINISHED FLOOR. NOTIFY THE ENGINEER OF ANY ROOMS WHERE THE PRECEDING LOCATION CANNOT BE MAINTAINED OR WHERE THERE IS A QUESTION ON LOCATION.
 - ALL DUCTWORK SHALL CLEAR DOORS AND WINDOWS.
 - ALL DUCTWORK DIMENSIONS, AS SHOWN ON THE DRAWINGS, ARE INTERNAL CLEAR DIMENSIONS AND DUCT SIZE SHALL BE INCREASED TO COMPENSATE FOR DUCT LINING THICKNESS.
 - PROVIDE ALL 90-DEGREE SQUARE ELBOWS WITH DOUBLE RADIUS TURNING VANES UNLESS OTHERWISE INDICATED. ELBOWS IN DISHWASHER, KITCHEN, AND LAUNDRY EXHAUSTS SHALL BE OF UN-VANED SMOOTH RADIUS CONSTRUCTION WITH A RADIUS EQUAL TO 1-1/2 TIMES THE WIDTH OF THE DUCT. PROVIDE ACCESS DOORS UPSTREAM OF ALL ELBOWS WITH TURNING VANES.
 - COORDINATE DIFFUSER, REGISTER, AND GRILLE LOCATIONS WITH ARCHITECTURAL REFLECTED CEILING PLANS, LIGHTING, AND OTHER CEILING ITEMS AND MAKE MINOR DUCT MODIFICATIONS TO SUIT.
 - FIELD-ERECTED AND FACTORY-ASSEMBLED AIR HANDLING UNIT COILS SHALL BE ARRANGED FOR REMOVAL FROM THE UPSTREAM SIDE WITHOUT DISMANTLING SUPPORTS. PROVIDE GALVANIZED STRUCTURAL STEEL SUPPORTS FOR ALL COILS (EXCEPT THE LOWEST COIL) IN BANKS OVER TWO COILS HIGH TO PERMIT THE INDEPENDENT REMOVAL OF ANY COIL.
 - ALL AIR HANDLING UNITS SHALL OPERATE WITHOUT MOISTURE CARRYOVER.
 - LOCATE ALL MECHANICAL EQUIPMENT (SINGLE DUCT, CONSTANT VOLUME, ETC.) FOR UNOBSTRUCTED ACCESS TO UNIT ACCESS PANELS, CONTROLS, AND VALVING.
 - PROVIDE FLEXIBLE CONNECTIONS IN ALL DUCTWORK SYSTEMS (SUPPLY, RETURN, AND EXHAUST) CONNECTED TO AIR

GO CAR WASH-INWOOD,
WV
 INWOOD-BERKELEY COUNTY, WV
MECHANICAL SYMBOLS LIST,
ABBREVIATIONS AND NOTES

Sheet Number

MO.1

HANDLING UNITS, FANS, AND OTHER EQUIPMENT THAT REQUIRE VIBRATION ISOLATION. FLEXIBLE CONNECTIONS SHALL BE PROVIDED AT THE POINT OF CONNECTION TO THE EQUIPMENT UNLESS OTHERWISE INDICATED.

16. UNLESS OTHERWISE NOTED, ALL DUCTWORK IS OVERHEAD, TIGHT TO THE UNDERSIDE OF THE STRUCTURE, WITH SPACE FOR INSULATION IF NEEDED.
17. RUNS OF FLEXIBLE DUCT SHALL NOT EXCEED 14 FT.
18. ALL DUCTWORK SHALL BE COORDINATED WITH ALL TRADES INVOLVED. OFFSETS IN DUCTS, INCLUDING DIVIDED DUCTS AND TRANSITIONS AROUND OBSTRUCTIONS, SHALL BE PROVIDED AT NO ADDITIONAL COST TO THE OWNER.
19. PROVIDE ACCESS DOORS IN DUCTWORK FOR THE OPERATION, ADJUSTMENT, AND MAINTENANCE OF ALL FANS, VALVES, AND MECHANICAL EQUIPMENT.
20. ALL DUCTS SHALL BE GROUNDED ACROSS FLEXIBLE CONNECTIONS WITH FLEXIBLE COPPER GROUNDING STRAPS. GROUNDING STRAPS SHALL BE BOLTED OR SOLDERED TO BOTH THE EQUIPMENT AND THE DUCT.
21. SEE SPECIFICATIONS FOR DUCTWORK GAUGES, BRACING, HANGERS, AND OTHER REQUIREMENTS.

SPECIFICATIONS

SECTION 0001 - NOTICE TO BIDDERS

- 1.1 BIDDERS REPRESENTATIONS
 - A. THE BIDDER BY MAKING A BID REPRESENTS THAT:
 - 1. THE BIDDER HAS READ AND UNDERSTANDS THE BIDDING DOCUMENTS, TO THE EXTENT THAT SUCH DOCUMENTATION RELATES TO THE WORK FOR WHICH THE BID IS SUBMITTED, AND FOR OTHER PORTIONS OF THE PROJECT, IF ANY, BEING BID CONCURRENTLY OR PRESENTLY UNDER CONSTRUCTION.
 - 2. THE BID IS MADE IN COMPLIANCE WITH THE BIDDING DOCUMENTS.
 - 3. THE SPECIFICATIONS AND DRAWINGS ARE INTENDED TO SERVE JOINTLY AS A BASIS FOR THE BIDDER TO SUBMIT A CONTRACT PRICE FOR THE MATERIAL AND LABOR.
 - 4. SHOULD CONFLICTS OR DISCREPANCIES OCCUR WITHIN THE BIDDING DOCUMENTS, THE ITEM OR ITEMS IN DISPUTE THAT REPRESENT THE GREATER COST SHALL PREVAIL IN THE FINAL BID.
 - 5. THE BID IS BASED UPON THE MATERIALS, EQUIPMENT AND SYSTEMS REQUIRED BY THE BIDDING DOCUMENTS WITHOUT EXCEPTION.
 - B. THE BIDDER HAS VISITED THE SITE, BECOME FAMILIAR WITH LOCAL CONDITIONS UNDER WHICH THE WORK IS TO BE PERFORMED AND HAS CORRELATED THE BIDDER'S PERSONAL OBSERVATIONS WITH THE REQUIREMENTS OF THE PROPOSED BIDDING DOCUMENTS.
 - C. THE BIDDER SHALL PROPOSE COORDINATION OF WORK SUCH THAT CONFLICTS WITH OTHER TRADES AND SPACE ALLOCATIONS ARE AVOIDED.
- 1.2 EXISTING CONDITIONS AND COORDINATION
 - A. THE BIDDER HAS VISITED THE SITE, BECOME FAMILIAR WITH LOCAL CONDITIONS UNDER WHICH THE WORK IS TO BE PERFORMED AND HAS CORRELATED THE BIDDER'S PERSONAL OBSERVATIONS WITH THE REQUIREMENTS OF THE PROPOSED BIDDING DOCUMENTS.
 - B. THE BIDDER SHALL PROPOSE COORDINATION OF WORK SUCH THAT CONFLICTS WITH OTHER TRADES AND SPACE ALLOCATIONS ARE AVOIDED.
- 1.3 RESPONSIBILITIES
 - A. THE BIDDER UNDERSTANDS THAT ANY CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR THE TIMELY COMPLETION AND ACCEPTANCE OF THEIR WORK AND THAT ANY ITEMS DAMAGED, LOST OR STOLEN DURING TIME OF CONSTRUCTION SHALL BE REPAIRED OR REPLACED WITHOUT ANY ADDITIONAL COST TO THE OWNER.
 - B. THE BIDDER UNDERSTANDS THAT ANY PROPOSED WORK IN OCCUPIED TENANT SPACES SHALL BE PERFORMED DURING TIMES OF NON-TENANT OCCUPANCY OR AS SCHEDULED OR DIRECTED BY THE BUILDING MANAGER.
 - C. THE BIDDER UNDERSTANDS THAT ANY PROPOSED SHUT-DOWN OF EXISTING SYSTEMS DURING CONSTRUCTION SHALL BE PRE-ARRANGED WITH THE BUILDING MANAGER AND THAT SUCH SHUT-DOWNS ARE TO BE KEPT TO A MINIMUM.

END OF SECTION 0001

SECTION 0102 -REQUIRED DOCUMENTS

- 1.1 SHOP DRAWINGS
 - A. A SET OF PRINTS FOR ANY MECHANICAL WORK INCLUDING BUT NOT LIMITED TO, DUCTWORK AND PIPING LAYOUT SHALL BE SUBMITTED FOR APPROVAL TO THE ENGINEER PRIOR TO CONSTRUCTION OR PURCHASE OF MATERIALS.
- 1.2 SUBMITTALS
 - A. EQUIPMENT SUBMITTALS OF ALL PROPOSED MECHANICAL AND ANCILLARY EQUIPMENT INCLUDING ALL ACCESSORIES SHALL BE SUBMITTED TO THE ENGINEER FOR REVIEW. ALL PERTINENT MODELS, SIZES, ACCESSORIES AND CHOICES SHALL BE CLEARLY CHECKED, PRINTED OR OTHERWISE INDICATED ON THE SUBMITTALS.
- 1.3 RECORD DRAWINGS
 - A. UPON COMPLETION OF THE WORK, A RECORD DRAWING SHALL BE SUBMITTED TO THE OWNER DEPICTING ALL SUBSEQUENT CHANGES, ADDITIONS AND OR CORRECTIONS TO THE CONTRACT DRAWINGS AND OR CONTRACT SCOPE MADE DURING CONSTRUCTION. THIS DRAWING SHALL REPRESENT A COMPLETE RECORD OF THE WORK INSTALLED.
- 1.4 EQUIPMENT OPERATING INSTRUCTIONS
 - A. ON COMPLETION AND ACCEPTANCE OF WORK, THIS CONTRACTOR SHALL FURNISH WRITTEN INSTRUCTIONS, EQUIPMENT MANUALS AND DEMONSTRATE TO THE OWNER THE PROPER OPERATION AND MAINTENANCE OF ALL EQUIPMENT AND APPARATUS FURNISHED UNDER THIS CONTRACT.
 - B. THESE INSTRUCTIONS SHALL BE TYPED ON 8-1/2 IN. X 11 IN. PAPER AND BOUND IN THREE-RING BINDERS WITH CLEAR ACETATE COVERS. THE CONTRACTOR SHALL GIVE THREE COPIES OF THE INSTRUCTIONS TO THE OWNER AND ONE ELECTRONIC COPY TO THE ENGINEER.
 - C. THE INSTRUCTION BOOKLET SHALL BE ORGANIZED IN SECTIONS, WITH ONE SECTION PER SYSTEM. THE COVER OF THE INSTRUCTION BOOKLET SHALL BEAR THE NAME, ADDRESS AND PHONE NUMBER OF THE PROJECT, ARCHITECT, ENGINEER, MECHANICAL CONTRACTOR AND SUBCONTRACTORS.

END OF SECTION 0102

SECTION 230593 - TESTING, ADJUSTING, AND BALANCING FOR HVAC

- 1.1 SUMMARY
 - A. TESTING, ADJUSTING, AND BALANCING FOR THE FOLLOWING:
 1. AIR SYSTEMS: CONSTANT-VOLUME SYSTEMS.
- 1.2 QUALITY ASSURANCE
 - A. THE CONTRACTOR SHALL PROCURE THE SERVICES OF A TESTING, ADJUSTING AND BALANCING (TAB) SPECIALIST WHO SPECIALIZES IN HEATING, VENTILATION AND AIR CONDITIONING SYSTEMS. THE TAB AGENT SHALL HAVE THE FOLLOWING QUALIFICATIONS: AABC, NEBB OR TABB CERTIFIED.
- 1.3 EXECUTION
 - A. THE TAB SPECIALIST SHALL PERFORM FLOW MEASUREMENTS OF ALL EXISTING AIR SYSTEMS THAT ARE TO REMAIN OR TO BE INCORPORATED INTO NEW WORK PRIOR TO THE STARTING OF WORK IN THE PROJECT SCOPE. A REPORT OF THESE MEASUREMENTS, INDICATING ANY AND ALL DEFICIENCIES SHALL BE SUBMITTED FOR OWNER REVIEW.
 - B. THE TAB SPECIALIST SHALL PERFORM FLOW MEASUREMENTS OF ALL NEW AIR SYSTEMS AS LISTED ABOVE IN THE PROJECT SCOPE. A REPORT OF THESE MEASUREMENTS, INDICATING ANY AND ALL DEFICIENCIES SHALL BE SUBMITTED FOR OWNER REVIEW.
 - C. THE REPORT SHALL INDICATE A SCHEMATIC DIAGRAM INDICATING LOCATIONS OF ALL EQUIPMENT TESTED AND MEASUREMENT LOCATIONS.
 - D. PRIOR TO FINAL INSPECTION OF THE WORK, THE TAB SPECIALIST SHALL BALANCE ALL SYSTEMS AS INDICATED ABOVE TO THE REQUIREMENTS OF THE DESIGN.
 - E. THE CONTRACTOR SHALL HAVE FURNISH AND INSTALL ALL ADDITIONAL BALANCING EQUIPMENT, PRESSURE TAPS, GAUGES AND OTHER EQUIPMENT AS REQUIRED FOR A PROPERLY BALANCED SYSTEM AT NO ADDITIONAL COST TO THE OWNER. SUCH ADDITIONAL EQUIPMENT SHALL ADHERE IN STRICT ACCORDANCE WITH THE RESPECTIVE EQUIPMENT MANUFACTURER'S RECOMMENDATIONS.
 - F. THE CONTRACTOR SHALL HAVE THE TESTING AND BALANCING SPECIALIST COORDINATE ALL WORK OF THIS SECTION WITH THE BUILDING MANAGER. BALANCING WORK SHALL NOT CONFLICT WITH OTHER WORK SO AS TO MAINTAIN COMPLETION WITHIN THE SPECIFIED TIME.
 - G. ALL INSTRUMENTS USED FOR TAB SHALL BE MAINTAINED IN GOOD WORKING CONDITION AND ACCURATELY CALIBRATED.
 - H. TOLERANCES: PLUS OR MINUS 5 PERCENT OF DESIGN VALUES.
 - I. INSPECTIONS: RANDOM CHECKS BY OWNER OR ARCHITECT TO VERIFY FINAL TESTING, ADJUSTING, AND BALANCING REPORT.
 - J. ADDITIONAL TESTS: RANDOM TESTS WITHIN 90 DAYS OF COMPLETING TAB TO VERIFY BALANCE CONDITIONS AND SEASONAL TESTS.

END OF SECTION 230593

SECTION 233113 - METAL DUCTS

- 1.1 CONSTRUCTION
 - A. EACH DUCT SYSTEM SHALL BE CONSTRUCTED FOR THE SPECIFIC SMACNA DUCT PRESSURE CLASSIFICATIONS SHOWN ON THE CONTRACT DRAWINGS. WHERE NO PRESSURE CLASSES ARE SPECIFIED BY THE DESIGNER, THE SMACNA 2-1/2 INCH WG PRESSURE CLASS IS THE BASIS OF COMPLIANCE WITH THESE STANDARDS, REGARDLESS OF THE VELOCITY IN THE DUCT.
 - B. ALL DUCTWORK SHALL BE CONSTRUCTED TO SMACNA 2" WG DESIGN AND NOT LESS THAN THE FOLLOWING STANDARDS:
 1. DUCTWORK SHALL BE TRANSVERSELY JOINTED BY CONNECTING SEAMS OF COMPANION ANGLES, FORMED FROM 1-1/2"x1-1/2"x1/8" GALVANIZED ANGLES, TACK-WELDED OR RIVETED TO THE DUCT. THE ANGLE FRAME SHALL BE CONTINUOUSLY FLANGED UP INTO UPRIGHT OF ANGLE AND EACH CORNER SHALL BE FILLED IN AND GROUND SMOOTH. JOINTS SHALL BE GASKETED WITH 1/8" THICK REINFORCED GASKET, OVERLAPPED AT CORNERS, GASKET SIMILAR TO 3M-1202 OR APPROVED EQUAL.
 2. RECTANGULAR FITTINGS AND ALL TRANSITION PIECES FROM RECTANGULAR TO ROUND SHALL BE NO. 16 GAUGE ALL WELDED CONSTRUCTION.
 3. HORIZONTAL DUCTS SHALL BE SUPPORTED ON NOT MORE THAN 6' CENTERS. VERTICAL RISERS SHALL BE SUPPORTED AT EACH FLOOR.
 4. LONGITUDINAL SEAMS FOR RECTANGULAR DUCTWORK SHALL BE PITTSBURGH LOCK SEAMS WITH SEALING COMPOUND, EQUAL TO BENJAMIN FOSTER NO. 30-03 INSERTED INTO SEAM. ALL SEAMS SHALL BE BRUSHED WITH NO. 30-02 AND COVERED WITH APPROVED SEALING TAPE.
 5. RECTANGULAR DUCTWORK 18 GAUGE AND HEAVIER FILLER RODS SHALL BE IN ACCORDANCE WITH SPECIFICATIONS FOR IRON AND STEEL GAS WELDING RODS, ASTM 215; AWG A3.2.
 6. ALL FITTINGS SUCH AS ELBOWS, TEES, ETC., SHALL BE NO. 20 GAUGE ZINC COATED STEEL. ELBOWS SHALL BE OF FIVE (5) PIECE WELDED AIRTIGHT CONSTRUCTION.
 - C. WHERE LATEST EDITION OF SMACNA DOES NOT CLEARLY STATE GAUGES AND/OR STIFFENERS TO BE USED OR, WHERE SMACNA STANDARDS REQUIRE INTERPRETATION, THE FOLLOWING MINIMUM METAL GAUGES AND BRACING SHALL BE USED:

USG	MAX. SIDE INCHES	TRANSVERSE JOINTS AND BRACING
22	UP TO 12	S SLIP, DRIVE SLIP, ONE INCH POCKET LOCK ON 8 FOOT CENTERS
22	13 TO 24	1"x1"x1/8" ANGLES ON 4 FOOT CENTERS
20	25 TO 35	1"x1"x1/8" ANGLES ON 2 FOOT CENTERS

END OF SECTION 233113

D. ALL DUCTWORK SHALL BE SEALED TO CLASS "A" AND LEAK TESTED TO MEAT SMACNA CLASS 6 FOR RECTANGULAR AND CLASS 3 FOR ROUND DUCTS.

- 1.2 MATERIALS
 - A. SINGLE-WALL RECTANGULAR DUCTS AND FITTINGS.
 - B. DOUBLE-WALL RECTANGULAR DUCTS AND FITTINGS.
 1. FIBROUS-GLASS OR FLEXIBLE ELASTOMERIC DUCT LINER FOR INTERSTITIAL INSULATION.
 2. PERFORATED INNER DUCT.
 - C. SINGLE-WALL ROUND AND FLAT-OVAL DUCTS AND FITTINGS.
 - D. DOUBLE-WALL ROUND AND FLAT-OVAL DUCTS AND FITTINGS.
 1. FIBROUS-GLASS OR FLEXIBLE ELASTOMERIC DUCT LINER FOR INTERSTITIAL INSULATION.
 2. PERFORATED INNER DUCT.
 - E. SHEET METAL MATERIALS:
 1. GALVANIZED SHEET STEEL.
 2. PVC-COATED, GALVANIZED SHEET STEEL.
 3. CARBON-STEEL SHEETS.
 4. STAINLESS-STEEL SHEETS.
 5. ALUMINUM SHEETS.
 6. FACTORY-APPLIED ANTI-MICROBIAL COATING.
 - F. DUCT LINER:
 1. FIBROUS GLASS, TYPE I, FLEXIBLE.
 - a. WITH ANTI-MICROBIAL EROSION-RESISTANT COATING.
 2. FLEXIBLE ELASTOMERIC.
 3. NATURAL FIBER.
 - G. SEALANT MATERIALS:
 1. TWO-PART TAPE SEALING SYSTEM.
 2. WATER-BASED JOINT AND SEAM SEALANT.
 3. SOLVENT-BASED JOINT AND SEAM SEALANT.
 4. FLANGED JOINT SEALANT.
 5. FLANGE GASKETS.
 6. ROUND DUCT JOINT O-RING SEALS.
- 1.4 DUCT CLEANING
 - A. CLEAN EXISTING DUCT SYSTEM(S) BEFORE TESTING, ADJUSTING, AND BALANCING.
 - B. CLEAN THE FOLLOWING ITEMS:
 1. AIR OUTLETS AND INLETS.
 2. SUPPLY, RETURN, AND EXHAUST FANS.
 3. COILS AND RELATED COMPONENTS.
 4. RETURN-AIR DUCTS, DAMPERS, ACTUATORS, AND TURNING VANES.
 5. SUPPLY-AIR DUCTS, DAMPERS, ACTUATORS, AND TURNING VANES.
 6. DEDICATED EXHAUST AND VENTILATION COMPONENTS AND MAKEUP AIR SYSTEMS.

END OF SECTION 230713

SECTION 230713 - DUCT INSULATION

- 1.1 QUALITY ASSURANCE
 - A. ALL DUCTS SHALL BE GALVANIZED STEEL EXCEPT AS FOLLOWS:
 1. MOIST ENVIRONMENT DUCT MATERIAL: ALUMINUM.
 - END OF SECTION 233113
 - 1.2 FIELD QUALITY CONTROL
 - A. FIELD INSPECTIONS: BY OWNER-ENGAGED AGENCY.
 - 1.3 INDOOR DUCT AND PLENUM INSULATION SCHEDULE:
 - A. CONCEALED, RECTANGULAR, ROUND AND FLAT-OVAL SUPPLY-RETURN, OUTDOOR-AND EXHAUST-AIR DUCT AND AIR PLENUM INSULATION:
 - B. FLEXIBLE ELASTOMERIC, MINERAL-FIBER BLANKET, MINERAL-FIBER BOARD OR POLYOLEFIN WITH MINIMUM INSTALLED THERMAL RESISTANCE AS FOLLOWS:

UNCONDITIONED SPACES WITHIN BUILDING:	R-3.5
WITHIN BUILDING ENVELOPE ASSEMBLY:	R-6
OUTSIDE OF BUILDING:	R-6
- 1.4 ITEMS NOT INSULATED:
 1. FIBROUS-GLASS DUCTS.
 2. METAL DUCTS WITH DUCT LINER OR SUFFICIENT THICKNESS TO COMPLY WITH ENERGY CODE AND ASHRAE/IESNA 90.1.
 3. FACTORY-INSULATED FLEXIBLE DUCTS.
 4. FACTORY-INSULATED PLENUMS AND CASINGS.
 5. FLEXIBLE CONNECTORS.
 6. VIBRATION-CONTROL DEVICES.
 7. FACTORY-INSULATED ACCESS PANELS AND DOORS.
 8. DUCTS THAT HAVE INTERNAL ACOUSTICAL LINING.
- 1.5 PRODUCTS
 - A. THE FOLLOWING INSULATION MANUFACTURERS WILL BE ACCEPTABLE:
 1. JOHNS-MANVILLE
 2. OWENS-CORNING

1.6 ACOUSTICAL TREATMENT

1. WHERE SHOWN ON THE DRAWINGS, LOW PRESSURE DUCTWORK SHALL BE LINED WITH 1.5" THICK R-6 AS MANUFACTURED BY DUCTMATE. 1-1/2 POUND MINIMUM DENSITY. NEOPRENE COATED, FLEXIBLE FIBERGLASS DUCT LINER. LINING SHALL COMPLY WITH NFPA 90A AND SHALL HAVE A FLAME SPREAD CLASSIFICATION OF NOT MORE THAN 25 AND A SMOKE DEVELOPED RATING NOT MORE THAN 50. DUCT SIZES WHERE LINING IS INDICATED ON PLANS ARE MINIMUM INSIDE CLEAR DIMENSIONS REQUIRED.

END OF SECTION 230713

SECTION 233713 - DIFFUSERS, REGISTERS, AND GRILLES

- 1.1 PRODUCTS
 - A. DIFFUSERS, REGISTERS AND GRILLES SHALL BE FURNISHED AND INSTALLED FOR CAPACITIES AND IN LOCATIONS INDICATED ON DRAWINGS. ALL REGISTERS AND DIFFUSERS SHALL BE PRIME COATED STEEL OR EXTRUDED ALUMINUM FINISHED UNLESS OTHERWISE NOTED IN BAKED WHITE ENAMEL.
 - B. MANUFACTURERS: TITUS
 1. SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCT BY ONE OF THE FOLLOWING:
 - a. CARNES.
 - b. HART & COOLEY INC.
 - c. KRUEGER.
 - d. METALAIRE, INC.
 - e. NAILOR INDUSTRIES INC.
 - C. ALL DIFFUSERS SHALL HAVE CONTROLLING/EQUALIZING GRID AND OPPOSED BLADE DAMPER UNLESS OTHERWISE NOTED.
 - D. ALL DUCTED RETURN REGISTERS SHALL HAVE AN OPPOSED BLADE DAMPER UNLESS OTHERWISE NOTED.

END OF SECTION 233713

THERMOSTATIC CONTROLS:

- A. GENERAL:
 1. THE SUPPLY OF HEATING AND COOLING ENERGY TO EACH ZONE SHALL BE INDIVIDUALLY CONTROLLED BY THERMOSTATIC CONTROLS RESPONDING TO TEMPERATURE WITHIN THE ZONE. FOR THE PURPOSES OF SECTION 6.4.3.1, A DWELLING UNIT SHALL BE PERMITTED TO BE CONSIDERED A SINGLE ZONE.
 - B. DEADBAND:
 1. WHERE USED TO CONTROL BOTH HEATING AND COOLING, ZONE THERMOSTATIC CONTROLS SHALL BE CAPABLE OF PROVIDING A TEMPERATURE RANGE OR DEAD BAND OF AT LEAST 5°F WITHIN WHICH THE SUPPLY OF HEATING AND COOLING ENERGY TO THE ZONE IS SHUT OFF OR REDUCED TO A MINIMUM.
 - EXCEPTIONS:
 1. THERMOSTATS THAT REQUIRE MANUAL CHANGEOVER BETWEEN HEATING AND COOLING MODES.
 - C. SETBACK CONTROLS:
 1. HEATING SYSTEMS LOCATED IN CLIMATE ZONES 2-8 SHALL BE EQUIPPED WITH CONTROLS THAT HAVE THE CAPABILITY TO AUTOMATICALLY RESTART AND TEMPORARILY OPERATE THE SYSTEM AS REQUIRED TO MAINTAIN ZONE TEMPERATURES ABOVE A HEATING SETPOINT ADJUSTABLE DOWN TO 55°F OR LOWER. COOLING SYSTEMS LOCATED IN CLIMATE ZONES 1B, 2B, AND 3B SHALL BE EQUIPPED WITH CONTROLS THAT HAVE THE CAPABILITY TO AUTOMATICALLY RESTART AND TEMPORARILY OPERATE THE SYSTEM AS REQUIRED TO MAINTAIN ZONE TEMPERATURES BELOW A COOLING SETPOINT ADJUSTABLE UP TO 90°F OR HIGHER OR TO PREVENT HIGH SPACE HUMIDITY LEVELS.
 - D. AUTOMATIC SHUTDOWN:
 1. HVAC SYSTEMS SHALL BE EQUIPPED WITH AT LEAST ONE OF THE FOLLOWING:
 1. CONTROLS THAT CAN START AND STOP THE SYSTEM UNDER DIFFERENT TIME SCHEDULES FOR SEVEN DIFFERENT DAY-TYPES PER WEEK, ARE CAPABLE OF RETAINING PROGRAMMING AND TIME SETTING DURING LOSS OF POWER FOR A PERIOD OF AT LEAST TEN HOURS, AND INCLUDE AN ACCESSIBLE MANUAL OVERRIDE, OR EQUIVALENT FUNCTION, THAT ALLOWS TEMPORARY OPERATION OF THE SYSTEM FOR UP TO TWO HOURS.
 - EXCEPTION:
 1. RESIDENTIAL OCCUPANCIES MAY USE CONTROLS THAT CAN START AND STOP THE SYSTEM UNDER TWO DIFFERENT TIME SCHEDULES PER WEEK.
 2. SETPOINT OVERLAP RESTRICTION:
 1. WHERE HEATING AND COOLING TO A ZONE ARE CONTROLLED BY SEPARATE ZONE THERMOSTATIC CONTROLS LOCATED WITHIN THE ZONE, MEANS (SUCH AS LIMIT SWITCHES, MECHANICAL STOPS, OR, FOR DDC SYSTEMS, SOFTWARE PROGRAMMING) SHALL BE PROVIDED TO PREVENT THE HEATING SETPOINT FROM EXCEEDING THE COOLING SETPOINT MINUS ANY APPLICABLE PROPORTIONAL BAND.
 3. HEAT PUMP SUPPLEMENTARY HEAT :
 1. HEAT PUMPS HAVING SUPPLEMENTARY ELECTRIC RESISTANCE HEAT SHALL HAVE CONTROLS THAT, EXCEPT DURING DEFROST, PREVENT SUPPLEMENTARY HEAT OPERATION WHERE THE HEAT PUMP CAN PROVIDE THE HEATING LOAD.

PIPING INSULATION

- A. INSULATE ALL PIPING IN ACCORDANCE WITH INSULATION SCHEDULE EXCEPT AS OTHERWISE NOTED.


SERVICE	INSULATION SCHEDULE - PIPING	SIZE	THICKNESS	MATERIAL FINISH
REFRIGERANT PIPING		1.0"		P-6
CONDENSER DRAIN PIPING (IF RUNNING THROUGH EXTERIOR WALL)		1.0"		P-6

 - B. PIPING, VALVES AND FITTINGS TO BE INSULATED:
 - 1) LOW TEMPERATURE PIPING SYSTEMS - 0 TO 60 DEG F INCLUDING:
 - a. CONDENSATE DRAIN PIPING.
 - 3) PROTECTIVE COVERINGS SHALL BE INSTALLED ON AREAS OF INSULATION THAT ARE EXPOSED TO WEATHER OR SUBJECT TO MECHANICAL DAMAGE. THE PROTECTIVE COVERING SHALL BE:
 - a. ARMA-CHEK SILVER MULTI-LAYER LAMINATE OF ALUMINUM, COATED WITH A UV PROTECTIVE FILM AND BACKED WITH A FLEXIBLE PVC FILM. THE MATERIAL SHOULD BE ADHERED WITH ARMAFLEX 520 ADHESIVE OR EQUIVALENT. AND ALL JOINTS AND SEAMS SECURED WITH ARMA-CHEK SILVER TAPE. INSTALLATION SHALL BE IN ALL CASES TO THE MANUFACTURER'S RECOMMENDATIONS.
 - OR
 - b. HIGH DENSITY RUBBER CLADDING OF THE "ARMA-CHEK" R TYPE BONDED USING AN APPROPRIATE FULL CONTACT ADHESIVE WITH A MINIMUM 50 MM OVERLAP AT ALL BUTT JOINTS AND LONGITUDINAL SEAMS. A WEATHER-PROOF MASTIC SEALANT SHALL BE APPLIED OVER ALL SEAMS AND JOINTS. ALL MATERIAL SHALL BE OVERLAPPED AND STAGGERED IN SUCH A WAY AS TO ENSURE A WEATHERSHED IS ALWAYS PROVIDED. INSTALLATION SHALL BE IN ALL CASES TO THE MANUFACTURER'S RECOMMENDATIONS. ALL EXCESS ADHESIVE VISIBLE ON THE SURFACE OF THE COMPLETED ASSEMBLY SHALL BE REMOVED USING AN APPROPRIATE CLEANING MATERIAL.
 - OR
 - c. METAL CLADDING, COMPRISED OF COATED SHEET METAL WITH ALL EXTERNAL JOINTS AND FIXING MADE WEATHER-PROOF WITH SILICONE SEALANT.

GO CAR WASH-INWOOD, CA
MECHANICAL SPECIFICATIONS

Sheet Number

MO.2




1 MECHANICAL FLOOR PLAN
1/8" = 1'-0"

- MECHANICAL GENERAL NOTES**
- A. EQUIPMENT SIZES, DIMENSIONS AND REQUIRED CONNECTIONS SHALL BE VERIFIED WITH THE ACTUAL EQUIPMENT SELECTED. VENDOR DRAWINGS BEFORE FABRICATION OF DUCTWORK, PIPING ETC.
 - B. CONTRACTOR SHALL COORDINATE ALL ELECTRICAL REQUIREMENTS FOR ALL HVAC BASED ON ACTUAL EQUIPMENT SELECTED PRIOR TO INSTALLATION.
 - C. CONTRACTOR SHALL COORDINATE EQUIPMENT WEIGHTS AND SUPPORTS BASED ON ACTUAL EQUIPMENT SELECTED.
 - D. COORDINATE WITH ALL TRADES FOR MATERIALS IN RATED AND PLENUM SPACES.
 - E. CONDENSATE DRAIN LINES SHALL BE PROVIDED FOR ALL MECHANICAL EQUIPMENT WHICH PRODUCES CONDENSATE.
 - F. PROVIDE WEATHER PROOF COATING FOR ALL EXTERIOR PIPING INSULATION.
 - G. COORDINATE ALL EQUIPMENT WITH STRUCTURAL ENGINEER AND THEIR DRAWINGS.
 - H. PROVIDE R-3.5 INSULATION WITH 1.5" THICKNESS FOR SUPPLY AND RETURN DUCTS.
 - I. PROVIDE R-6 INSULATION WITH 2" THICKNESS FOR ALL OUTDOOR AIR INTAKE DUCTS.

- MECHANICAL FLOOR PLAN KEY NOTES:**
- 1 EXTEND 1" CONDENSATE DRAIN LINE TO EXTERIOR WALL. TURN DOWN IN WALL TO APPROXIMATELY 18" ABOVE GRADE. PENETRATE WALL AND PROVIDE 90 DEG ELBOW. SPILL CONDENSATE ON GRADE. CONDENSATE PIPING SHALL BE PVC.
 - 2 LOCATION OF DIGITAL THERMOSTAT CONTROL. INSTALL AND WIRE NEW 7-DAY PROGRAMMABLE THERMOSTAT. COORDINATE EXACT LOCATION WITH ARCHITECT AND OWNER PRIOR TO ROUGH-IN. PROVIDE LOCKABLE COVER.
 - 3 EXTEND REFRIGERANT PIPING FROM AHU-1(N) TO EXTERIOR WALL. TURN PIPING IN WALL AND EXTEND TO CU-1(N). REFRIGERANT PIPING TO BE SIZED PER MANUFACTURER'S RECOMMENDATIONS. PIPING EXPOSED TO WEATHER SHALL BE PROTECTED FROM DAMAGE DUE TO SUNLIGHT, MOISTURE, EQUIPMENT MAINTENANCE AND SHALL PROVIDE SHIELDING FROM SOLAR RADIATION THAT CAN CAUSE DEGRADATION. ADHESIVE TAPERS ARE NOT PERMITTED.
 - 4 MOTORIZED DAMPER TO BE INTERLOCKED WITH AHU-1(N).
 - 5 PROVIDE WITH WALL THIMBLE, COMMON VENTING AND SIDEWALL VENT KITS. VENT SHALL BE DOUBLE WALL TYPE B-VENT.


COMBUSTION AIR CALCULATIONS:	
PER PARAGRAPH 304.5.1 WEST VIRGINIA GAS FUEL CODE MINIMUM REQUIRED VOLUME OF COMBUSTION AIR SHALL BE 50 CF PER 1000 BTUH INPUT.	
RTH-1(N) & RTH-2(N) IN TUNNEL.	125,000 BTUH X 2 = 250,000 BTUH
	250,000 BTUH / 1000 BTUH = 250 BTUH X 50 CF/BTUH = 12,500 CF.
TUNNEL = 116'x24'x14'	= 38976 CF - SUFFICIENT COMBUSTION AIR AVAILABLE.
UH-1(N) & UH-2(N) PROVIDED WITH SEPARATE VENT AND INTAKE .	
B-1(N) PROVIDED WITH SEPARATE VENT AND INTAKE .	




2 MECHANICAL ROOF PLAN
1/8" = 1'-0"

- MECHANICAL GENERAL NOTES**
- A. EQUIPMENT SIZES, DIMENSIONS AND REQUIRED CONNECTIONS SHALL BE VERIFIED WITH THE ACTUAL EQUIPMENT SELECTED. VENDOR DRAWINGS BEFORE FABRICATION OF DUCTWORK, PIPING ETC.
 - B. CONTRACTOR SHALL COORDINATE ALL ELECTRICAL REQUIREMENTS FOR ALL HVAC BASED ON ACTUAL EQUIPMENT SELECTED PRIOR TO INSTALLATION.
 - C. CONTRACTOR SHALL COORDINATE EQUIPMENT WEIGHTS AND SUPPORTS BASED ON ACTUAL EQUIPMENT SELECTED.
 - D. COORDINATE WITH ALL TRADES FOR MATERIALS IN RATED AND PLENUM SPACES.
 - E. CONDENSATE DRAIN LINES SHALL BE PROVIDED FOR ALL MECHANICAL EQUIPMENT WHICH PRODUCES CONDENSATE.
 - F. PROVIDE WEATHER PROOF COATING FOR ALL EXTERIOR PIPING INSULATION.
 - G. COORDINATE ALL EQUIPMENT WITH STRUCTURAL ENGINEER AND THEIR DRAWINGS.
 - H. PROVIDE R-3.5 INSULATION WITH 1.5" THICKNESS FOR SUPPLY AND RETURN DUCTS.
 - I. PROVIDE R-6 INSULATION WITH 2" THICKNESS FOR ALL OUTDOOR AIR INTAKE DUCTS.

- MECHANICAL ROOF PLAN KEY NOTES:**
- 1 TERMINATE EXHAUST 3' AWAY FROM LOT LINE AND ANY BUILDING OPENING.
 - 2 PROVIDE 3' VERTICAL SEPARATION BETWEEN INTAKE AND EXHAUST VENT.



1 A.C. UNIT INSTALLATION DETAIL
M5.1 N.T.S




TYPICAL TRAPEZE HANGER SUPPORT


PIPE HANGER ROD AND SPACING SCHEDULE											
NOMINAL PIPE OR TUBE SIZE - INCHES	5/8	3/4	7/8	1	1 1/2	2	2 1/2	-	-	-	-
HANGER ROD SIZES INCHES	3/8	3/8	3/8	3/8	3/8	3/8	3/8	-	-	-	-
MAX. SPACING BETWEEN PIPE SUPPORTS - FEET	-	6	-	7	9	10	11	-	-	-	-
MAX. SPACING BETWEEN CU. TUBE SUPPORTS-FT.	6	6	6	6	8	9	10	-	-	-	-

NOTES : TRAPEZE HANGER SPACING SHALL BE BASED ON SPACING OF SMALLEST PIPE ON TRAPEZE. TRAPEZE SHALL BE DESIGNED WITH A FACTOR OF SAFETY OF 5 FOR CENTER OF SPAN CONCENTRATED LOAD.


2 METHOD OF HANGING REFRIGERANT PIPING
M5.1 N.T.S




3 CEILING EXHAUST FAN
M5.1 N.T.S



4 MOTORIZED DAMPER DETAIL
M5.1 N.T.S



5 DETAIL OF PIPE SUPPORT DETAIL ON ROOF
M5.1 N.T.S



6 LOW PRESSURE BALANCING DAMPER
M5.1 N.T.S

AIR HANDLING UNIT SPLIT SYSTEM SCHEDULE																	
TAG	MANUFACTURER	MODEL	LOCATION	COOLING TOTAL MBH	HEATING TOTAL MBH	ESP (in. WG)	AIR FLOW (CFM)		REFRIGERANT PIPING		ELECTRICAL			AUXILIARY ELECTRIC HEAT		WEIGHT LBS	NOTES
							SUPPLY AIR	OUTSIDE AIR	LIQUID	GAS	V / PH/HZ	MCA (A)	MOCP (A)	V / PH	KW		
AHU-1(N)	CARRIER	FMC4Z1800 (OR EQUIVALENT)	SEE PLAN	17.7	12.5	0.5	600	70	3/8"	3/4"	208/1/60	2.6	15	208/1	6	85	1-5

NOTES:
1. UNIT SHALL HAVE TEN YEAR EXTENDED WARRANTY FOR COMPRESSORS/PARTS.
2. PROVIDE COMPRESSOR CYCLE PROTECTOR.
3. CONTRACTOR SHALL PROVIDE A LONG LINE SET FOR REFRIGERANT PIPING IN THE EVENT THAT TOTAL REFRIGERANT LENGTH EXCEED THE MANUFACTURER'S STANDARD RECOMMENDED LENGTH.
4. INDOOR UNIT IS POWERED BY THE OUTDOOR UNIT.
5. PROVIDE SECONDARY DRAIN PAN WITH WATER LEAKAGE SENSOR TO SHUT DOWN THE UNIT IN CASE OF LEAKAGE.

SPLIT HEAT PUMP SYSTEM SCHEDULE															
TAG	MANUFACTURER	MODEL	LOCATION	COOLING TOTAL MBH	HEATING TOTAL MBH	ESP (in. WG)	REFRIGERANT PIPING		HSPF	SEER	ELECTRICAL			WEIGHT LBS	NOTES
							LIQUID	GAS			V / PH/HZ	MCA (A)	MOCP (A)		
CU-1(N)	CARRIER	25HBC518AP030	SEE PLAN	17.7	12.5	0.5	3/8"	3/4"	8.5	15.3	208/1/60	11.8	20	170	1-6

NOTES:
1. OUTDOOR CONDENSING UNITS TO BE LOCATED WITH PROPER CLEARANCES AND MUST PREVENT RE CIRCULATION OF AIR. COORDINATE WITH MANUFACTURER AND ARCHITECT AT THE TIME OF UNIT
2. UNIT SHALL HAVE TEN YEAR EXTENDED WARRANTY FOR COMPRESSORS/PARTS.
3. PROVIDE COMPRESSOR CYCLE PROTECTOR.
4. STAND TO BE PROVIDED BY MECHANICAL CONTRACTOR.
5. CONTRACTOR SHALL PROVIDE A LONG LINE SET FOR REFRIGERANT PIPING IN THE EVENT THAT TOTAL REFRIGERANT LENGTH EXCEED THE MANUFACTURER'S STANDARD RECOMMENDED LENGTH.

EXHAUST FAN SCHEDULE													
TAG	QUANTITY	FLOW RATE CFM	EXTERNAL STATIC PRESSURE IN W.G.	SPEED RPM	ELECTRIC DATA			MAXIMUM LOUDNESS DBA	BASIS OF DESIGN		WEIGHTS (LBS)	NOTES	REMARK
					V/PH/HZ	Watts (W)	FLA (AMPS)		MANUFACTURER	MODEL			
TEF-1(N)	1	70	0.6	1664	115/1/60	12	0.29	39	GREENHECK	SP-A90-130-VG	12	1-3	NEW

NOTES:
1) PROVIDE FACTORY MOUNTED AND INSTALLED WEATHER PROOF DISCONNECT SWITCH.
2) PROVIDE THERMAL OVERLOAD PROTECTION, BACKDRAFT DAMPER.
3) PROVIDE ALL NECESSARY ACCESSORIES AS PER MANUFACTURER'S RECOMMENDATIONS.

MECHANICAL AIR TERMINAL DEVICES SCHEDULE					
TAG	SIZE	DESCRIPTION	BASIS OF DESIGN		NOTES
			MANUFACTURER	MODEL	
A	24X24	SUPPLY AIR DIFFUSER	TITUS	TMS	1,2,3,4,5
B	12X12	SUPPLY AIR DIFFUSER	TITUS	TMS	1,2,3,4,5
C	24X24	RETURN GRILLE	TITUS	50F	1,2,3,4,5
D	12x12	RETURN GRILLE	TITUS	50F	1,2,3,4,5

NOTES:
1. PROVIDE STANDARD WHITE FINISH FOR ALL AIR DEVICES UNLESS NOTED OTHERWISE ON PLAN.
2. COORDINATE FINAL COLOR/FINISH WITH ARCHITECT/OWNER.
3. PROVIDE FRAME FOR MOUNTING AIR DEVICE IN LAY-IN GRID CEILING UNLESS REFLECTED CEILING PLAN INDICATES HARD CEILING. IN AREAS WITH HARD CEILINGS, PROVIDE FRAMES FOR SURFACE MOUNTING.
4. UNLESS OTHERWISE NOTED, BRANCH DUCTS SERVING AIR DEVICES SHALL BE SAME SIZE AS NECK OF AIR DEVICE.
5. AIR DEVICE SHALL BE OF GALVANIZED FINISH WHEN INSTALLED ON EXPOSED DUCTWORK.
FOR ROUND NECK DIFFUSERS:
6" DIA: 0-100 CFM
8" DIA: 101-250 CFM

GAS FIRED UNIT HEATER SCHEDULE											
MARK	MANUFACTURER	MODEL	MBH INPUT	MBH OUTPUT	EFFICIENCY	CFM	ELECTRIC DATA			GAS PRESSURE (IN WC)	REMARK
							HP	VOLTAGE	PHASE		
UH-1(N)	MODINE	HD 60AS0111FBAN	60	49.2	82%	990	1/12	120	1	6-7	2
UH-2(N)	MODINE	HD 60AS0111FBAN	60	49.2	82%	990	1/12	120	1	6-7	2

NOTES:
1) PROVIDE WITH MOUNTING BRACKET, INTEGRAL THERMOSTAT AND A TRIP SWITCH. SWITCH SHALL ACTIVE THE FAN AND BURNER WHEN DOOR RISES.
2) PROVIDE WITH MOUNTING BRACKET AND INTEGRAL THERMOSTAT.

GAS FIRED RADIANT TUBE HEATER SCHEDULE										
MARK	MANUFACTURER	MODEL	MBH INPUT	STRAIGHT LENTH (FT)	AMPS	VOLTAGE	PHASE	GAS PRESSURE (IN WC)	WEIGHT (LBS)	REMARK
RTH-2(N)	RE VERBER RAY	DX2-50-125	125	50'8"	4.8	120	1	5-14	290	2

NOTES:
1) PROVIDE WITH MOUNTING BRACKET, INTEGRAL THERMOSTAT AND A TRIP SWITCH. SWITCH SHALL ACTIVE THE FAN AND BURNER WHEN DOOR RISES.
2) PROVIDE WITH MOUNTING BRACKET AND INTEGRAL THERMOSTAT.

BOILER SCHEDULE													
UNIT #	LOCATION	UNIT SERVING	TYPE	FUEL	MAX. FLOW RATE (GPM)	MIN. INPUT (MBH)	MAX. INPUT (MBH)	BOILER PRESSURE DROP FT.	ELECTRICAL REQUIREMENTS (V/HZ)	WEIGHT (LBS)	A.F.U.E.	BASIS OF DESIGN	
												MFR	MODEL
B-1(N)	FIRST FLOOR	RADIANT HEATING	MODULATING CONDENSING	GAS	15	15.5	155	3.5	120/60, <2.2 AMP	166	95	LOCHINVAR	WHB155N

NOTES :-
1) PROVIDE LOW-LOSS TEMPERATURE SENSOR.
2) PROVIDE OUTDOOR AIR SENSOR FOR OUTDOOR RESET CONTROL.
3) BOILERS SHALL BE PROVIDED WITH CONDENSATE NEUTRALIZER TO BE MANUFACTURED BY AXIOM NC-1 OR EQUIVALENT. CONDENSATE NEUTRALIZER/DRAIN/PUMP FOR EACH BOILER SYSTEM.
4) BOILER TO OPERATE ON OUTDOOR RESET CONTROL WITH FEEDBACK FROM OUTDOOR AIR TEMPERATURE SENSOR MOUNTED ON THE NORTH FAÇADE OF THE BUILDING PER MANUFACTURER GUIDELINES.

SCOPE OF WORK

USE OF NEW 800 AMP 480Y/277V - 3Ø ELECTRICAL SERVICE. PROVIDE NEW PANELS "MDP" AND "LV". PROVIDE ALL NECESSARY EQUIPMENT AND ALL WIRING AND LIGHTING FOR NEW SPACE. COORDINATE WITH G.C. FOR LOW VOLTAGE WIRING DETAIL.

POWER GENERAL NOTES

- A. VERIFY EXACT LOCATIONS OF HVAC AND PLUMBING EQUIPMENT, CONDUIT STUB-UPS AND POWER CONNECTIONS PRIOR TO ROUGH-IN.
- B. VERIFY EXACT LOCATION, MOUNTING HEIGHTS AND CONDUIT ROUTING FOR ALL THERMOSTATS, TEMPERATURE SENSORS, HUMIDISTATS AND CO₂ SENSORS PRIOR TO ROUGH-IN.
- C. REFER TO MECHANICAL AND PLUMBING DRAWINGS FOR ADDITIONAL ELECTRICAL REQUIREMENTS. COORDINATE PROVISIONS FOR CONTROL CONDUIT AND WIRING AS REQUIRED FOR INTERLOCKING OF FANS, MOTORS, ETC. REFER TO SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS.
- D. MOUNT DEVICES INSTALLED ON EQUIPMENT ON NON-REMOVABLE PANEL. COORDINATE LOCATION PRIOR TO COMMENCING ROUGH-IN WORK.
- E. REFER TO EQUIPMENT SPECIFICATIONS FOR DATA AND POWER REQUIREMENTS AND LOCATIONS OF ALL MENU BOARDS AND SIGNS.
- F. VERIFY MOUNTING HEIGHTS OF ALL RECEPTACLES WITH EQUIPMENT SUPPLIED PRIOR TO INSTALLATION.
- G. ALL EQUIPMENT ELECTRICAL OUTLETS ARE DIMENSIONED TO CENTERLINE OF BOX FROM ABOVE FINISHED FLOOR.
- H. ELECTRICAL CONTRACTOR TO PROVIDE CORD & PLUG CONNECTIONS FOR EQUIPMENT AS REQUIRED.
- I. ALL 120V, 20A OUTLETS IN THE FOOD PREP AREA SHALL BE GROUND FAULT INTERRUPT TYPE.
- J. PROVIDE "UP" OUTLET AT ROOFTOP EQUIPMENT.
- K. ROUTE ALL CONDUIT ROOF PENETRATIONS OUTSIDE OF CURB. DO NOT PENETRATE BOTTOM OF RTU UNITS AND EXHAUST FAN CURBS.

LOW VOLTAGE GENERAL NOTES

- A. ALL P.O.S. (POINT OF SALE) CIRCUITS SHALL HAVE AN ISOLATED GROUND WIRE BACK TO THE PANEL. ALL P.O.S. EQUIPMENT SHALL BE WIRED INDEPENDENTLY OF ANY NON-P.O.S. EQUIPMENT.
- B. ALL RECEPTACLES FOR P.O.S. EQUIPMENT SHALL BE ISOLATED GROUND WITH SURGE SUPPRESSOR TYPE. ALL RECEPTACLES FOR P.O.S. EQUIPMENT SHALL BE SINGLE UNIT, UNLESS A DUPLEX RECEPTACLE CAN BE USED TO SUPPLY TWO P.O.S. UNITS. DUPLEX RECEPTACLES MAY BE USED IN THE MANAGER'S OFFICE FOR NON-P.O.S. EQUIPMENT (COMPUTER, MUSIC, FIRE ALARM, SECURITY, ETC.).
- C. ALL CIRCUITS FOR P.O.S. EQUIPMENT SHALL BE CONNECTED TO THE SAME PHASE OF POWER IN THE PANEL. ALL BRANCH CIRCUIT BREAKERS SUPPLYING P.O.S. EQUIPMENT SHALL HAVE LOCKING HANDLE DEVICES.
- D. EACH RECEPTACLE TYPE (LOCKING OR STRAIGHT BLADE) SHALL MATCH THAT OF THE EQUIPMENT FURNISHED. WHERE P.O.S. EQUIPMENT IS FURNISHED WITHOUT A PLUG THE RECEPTACLE SHALL BE LOCKING TYPE. COORDINATE RECEPTACLE TYPES WITH THE P.O.S. EQUIPMENT SUPPLIER.

GENERAL ELECTRICAL NOTES

- A. INCLUDE ALLOWANCE FOR UNFORESEEN CONDITIONS THAT MAY AFFECT THE SCOPE OF WORK. MINOR DEVIATIONS REQUIRED FOR ACCOMPLISHING THE INTENT OF THIS DESIGN SHALL BE INCLUDED IN THE ALLOWANCE.
- B. SWITCHBOARDS, PANELBOARDS, DISCONNECT SWITCHES, TRANSFORMERS AND CONTACTORS SHALL BE "LISTED" AND "IDENTIFIED" AS RATED FOR MINIMUM OF 75°C CONDUCTOR TERMINATION.
- C. ELECTRICAL DESIGN IS BASED ON INSTALLATION OF 75°C CONDUCTORS CONNECTED TO TERMINAL LUGS AND EQUIPMENT U.L. LISTED FOR MINIMUM 75°C. CONDUCTORS TERMINATED ON EQUIPMENT WITH LOWER RATING (60°C) OR NO RATING SHOWN SHALL HAVE CONDUCTOR SIZE INCREASED TO CONFORM TO ADOPTED ELECTRICAL CODE AND UL/CUL NO. 489 REQUIREMENTS.
- D. CONDUIT INSTALLED INDOORS SHALL BE ELECTRICAL METALLIC TUBING (EMT), MINIMUM 1/2" OR AS NOTED.
- E. CONDUIT INSTALLED BELOW SLAB SHALL BE RIGID STEEL, IMC, PVC OR HDPE, MINIMUM 3/4". IF PVC OR HDPE IS USED, TRANSITION TO RIGID STEEL BEFORE TURNING UP AND PENETRATING FLOOR SLAB.
- F. CONDUCTORS SHALL BE MINIMUM #12 THHN/THWN COPPER UNLESS NOTED OTHERWISE ON PLANS OR IN SPECIFICATIONS. BRANCH CIRCUITS SHALL BE PROVIDED WITH (2) #12 CONDUCTORS AND (1) #12 EQUIPMENT GROUND CONDUCTOR UNLESS NOTED OTHERWISE.
- G. BRANCH CIRCUITS SHOWN WITH TWO GROUNDING CONDUCTORS SHALL HAVE ONE EQUIPMENT GROUND CONDUCTOR (GREEN) AND ONE ISOLATED GROUND CONDUCTOR (GREEN W/YELLOW STRIP) INSTALLED IN RACEWAY.
- H. DIRECT CURRENT WIRING SHALL BE (2) #10 IN 1/2" CONDUIT UNLESS NOTED OTHERWISE.
- I. CONTROL VOLTAGE WIRING SHALL BE PLENUM RATED OR INSTALLED IN CONDUIT.
- J. THERMOSTATS, TEMPERATURE SENSORS, CARBON DIOXIDE SENSORS AND HUMIDISTATS: UNLESS NOTED OTHERWISE, PROVIDE WALL BOX AT +3'-10" AFF WITH 1/2" CONDUIT STUBBED OUT TO ABOVE ACCESSIBLE CEILING WITH NYLON BUSHINGS AND PULLSTRING.
- K. PROVIDE FLEXIBLE CONNECTIONS ONLY FOR FINAL CONNECTION TO EQUIPMENT, 6"-0" MAXIMUM LENGTH. PROVIDE LIQUID TIGHT FLEXIBLE CONNECTION AT EXTERIOR LOCATIONS AND WHERE EXPOSURE TO MOISTURE IS POSSIBLE.
- L. ALL EMPTY CONDUITS SHALL BE PROVIDED WITH A PULL WIRE.
- M. ALL RACEWAYS SHALL CONTAIN A GROUNDING ELECTRODE SIZED PER THE ADOPTED ELECTRICAL CODE.
- N. COORDINATE WORK ABOVE THE CEILING WITH OTHER TRADES TO PROVIDE THE GREATEST POSSIBLE CLEARANCE. CONDUIT RUNS SHALL BE RUN THROUGH TRUSSES WHERE POSSIBLE.
- O. VERIFY EXACT PLACEMENT OF ALL DEVICES SHOWN ON CONSTRUCTION DOCUMENTS PRIOR TO FINAL PLACEMENT.
- P. ALL RECESSED PANELBOARDS SHALL BE INSTALLED WITH MINIMUM OF (3) 3/4" CONDUITS STUBBED UP TO ACCESSIBLE CEILING SPACE FOR FUTURE USE.
- Q. ALL PANELBOARDS, SWITCHBOARDS AND LINE VOLTAGE CONTROL EQUIPMENT SHALL BE FIELD MARKED TO WARN QUALIFIED PERSONS OF POTENTIAL ELECTRIC ARC FLASH HAZARDS. MARKING SHALL BE LOCATED SO AS TO BE CLEARLY VISIBLE TO QUALIFIED PERSONS BEFORE EXAMINATION, ADJUSTING, SERVICING OR MAINTENANCE OF EQUIPMENT. MARKING SHALL BE SELF-ADHESIVE, COMMERCIAL LABEL CONFORMING TO ADOPTED CODES.
- R. LIGHT SWITCHES, ELECTRICAL OUTLETS, THERMOSTATS AND OTHER ENVIRONMENTAL CONTROLS SHALL HAVE OPERABLE PARTS OF THE CONTROLS LOCATED NO HIGHER THAN 48" AND NO LOWER THAN 15" ABOVE THE FLOOR. IF THE REACH IS OVER AN OBSTRUCTION BETWEEN 20" AND 25" IN DEPTH, THE MAXIMUM HEIGHT IS REDUCED TO 44" FOR FORWARD APPROACH OR 46" FOR SIDE APPROACH, PROVIDED THE OBSTRUCTION IS NO MORE THAN 24" IN DEPTH. OBSTRUCTIONS SHALL NOT EXTEND MORE THAN 25" FROM THE WALL BENEATH A CONTROL.
- S. TERMS:
 SHALL - ACTION THAT IS REQUIRED WITHOUT OPTION OR QUALIFICATION.
 FURNISH - CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING.
 INSTALL - CONTRACTOR SHALL BE RESPONSIBLE FOR LABOR AND CONSTRUCTION EQUIPMENT NECESSARY TO SET IN PLACE, CONNECT, CALIBRATE AND/OR TEST EQUIPMENT FURNISHED BY HIM OR OTHERS.
 PROVIDE - CONTRACTOR SHALL FURNISH AND INSTALL.

LIGHTING GENERAL NOTES

- A. CONNECT EXIT SIGNS, EMERGENCY AND NIGHT LIGHTS TO UNSWITCHED LIGHTING CIRCUIT, NOT CONTROLLED BY OCCUPANCY SENSORS, SWITCHES OR CONTACTORS.
- B. PROVIDE DEDICATED NEUTRAL WITH ALL DIMMING SYSTEM CIRCUITS. NO COMMON NEUTRALS SHALL BE ALLOWED.
- C. REFER TO ARCHITECTURAL REFLECTED CEILING PLAN AND DETAILS FOR LOCATION OF ALL LIGHTING FIXTURES AND ALL OTHER EQUIPMENT INSTALLED IN THE CEILING SYSTEM. VERIFY MOUNTING HEIGHTS AND FINISHES WITH ARCHITECT PRIOR TO ROUGH-IN.
- D. REFER TO POWER PLANS FOR LOCATIONS OF ELECTRICAL EQUIPMENT.
- E. PROVIDE (2) ADDITIONAL #12 CONDUCTORS FOR ALL 0-10V DIMMING CIRCUITS.

POS LEGEND

	HOME RUN TO PANEL. CIRCUIT NUMBERS, PHASE, NEUTRAL AND GROUND CONDUCTORS INDICATED ALONG WITH ISOLATED GROUND CONDUCTOR IF APPLICABLE.
	PARTIAL CIRCUIT
	CONDUIT INSTALLED CONCEALED ABOVE CEILING OR IN WALL
	CONDUIT INSTALLED CONCEALED BELOW FLOOR SLAB OR UNDERGROUND
	CONDUIT INSTALLED WITH DIRECT CURRENT POWER WIRING
	CONDUIT TURNED UP OR DOWN AS NOTED
	SINGLE POLE SWITCH, +3'-10" OR AS NOTED
	THREE-WAY SWITCH, +3'-10" OR AS NOTED
	WEATHERPROOF TOGGLE SWITCH, +3'-10" OR AS NOTED
	KEYED SWITCH, +3'-10" OR AS NOTED
	CEILING MOUNTED DAYLIGHT SENSOR
	WALL MOUNTED OCCUPANCY SENSOR, +3'-10" OR AS NOTED
	CEILING MOUNTED OCCUPANCY SENSOR
	WALL MOUNTED VACANCY SENSOR, +3'-10" OR AS NOTED
	CEILING MOUNTED VACANCY SENSOR
	CEILING MOUNTED INTERIOR DAYLIGHT HARVESTING PHOTOCCELL SENSOR
	POWER PACK, INSTALLED ABOVE ACCESSIBLE CEILING
	SIMPLEX RECEPTACLE, +18" OR AS NOTED
	ISOLATED GROUND SIMPLEX RECEPTACLE, +18" OR AS NOTED
	DUPLEX RECEPTACLE, +18" OR AS NOTED
	ISOLATED GROUND DUPLEX RECEPTACLE, +18" OR AS NOTED
	CONTROLLED DUPLEX RECEPTACLE, +18" OR AS NOTED
	QUADRUPLX RECEPTACLE, +18" OR AS NOTED
	ISOLATED GROUND QUADRUPLX RECEPTACLE, +18" OR AS NOTED
	QUADRUPLX RECEPTACLE WITH ONE OUTLET CONTROLLED, +18" OR AS NOTED
	GROUND FAULT INTERRUPTING RECEPTACLE, +18" OR AS NOTED
	TAMPER RESISTANT RECEPTACLE, +18" OR AS NOTED
	WEATHERPROOF GROUND FAULT INTERRUPTING RECEPTACLE, +18" OR AS NOTED
	RECEPTACLE INSTALLED HORIZONTALLY, BOTTOM AT +6" ABOVE COUNTER TOP
	RECEPTACLE INSTALLED FLUSH IN CEILING
	ISOLATED GROUND RECEPTACLE INSTALLED FLUSH IN CEILING
	SPECIAL RECEPTACLE, NEMA STYLE AS NOTED, +18" OR AS NOTED
	JUNCTION BOX
	DISCONNECT SWITCH, TOP AT +6'-0" OR AS NOTED
	DISCONNECT SWITCH PROVIDED WITH EQUIPMENT.
	COMBINATION MOTOR STARTER/DISCONNECT SWITCH FURNISHED BY MECHANICAL CONTRACTOR, INSTALLED BY ELECTRICAL CONTRACTOR
	MOTOR CONNECTION
	LIGHTING CONTACTOR, INSTALLED AS NOTED
	TIME CLOCK, +6'-2" OR AS NOTED
	CONTROL OR POWER RELAY, INSTALLED AS NOTED
	PUSHBUTTON, TOP AT +4'-6" OR AS NOTED
	DOOR BELL CHIME, +6'-0" OR AS NOTED
	CONTROL TRANSFORMER, INSTALLED AS NOTED
	THERMOSTAT, TEMPERATURE SENSOR, CARBON DIOXIDE SENSOR AND HUMIDISTAT PROVIDED BY MECHANICAL CONTRACTOR, +3'-10" OR AS NOTED
	ELECTRICALLY OPERATED DAMPER, PROVIDED BY MECHANICAL CONTRACTOR
	DATA OUTLET, +18" WITH 3/4" CONDUIT TO ABOVE CEILING
	DATA OUTLET, +6" ABOVE COUNTER WITH 3/4" CONDUIT TO ABOVE CEILING
	TELEPHONE/DATA OUTLET, +18" WITH 1" CONDUIT TO ABOVE CEILING
	TELEPHONE/DATA OUTLET, +6" ABOVE COUNTER WITH 1" CONDUIT TO ABOVE CEILING
	FIRE ALARM CONTROL PANEL, FLUSH MOUNTED, TOP AT +6'-0"
	MANUAL FIRE ALARM PULL STATION, +3'-10" PER ADA
	FIRE ALARM HORN AND 75cd STROBE, +80" TO BOTTOM OF DEVICE PER ADA
	STROBE ONLY (75cd UNO), +80" TO BOTTOM OF DEVICE PER ADA
	FIRE ALARM HORN AND 115cd STROBE, CEILING MOUNTED
	STROBE ONLY (115cd UNO), CEILING MOUNTED
	AREA TYPE PHOTOELECTRIC SMOKE DETECTOR, CEILING MOUNTED, OR AS NOTED
	DUCT TYPE PHOTOELECTRIC SMOKE DETECTOR WITH SAMPLING TUBES AND REMOTE INDICATOR LIGHT MOUNTED FLUSH IN CEILING BELOW DETECTOR
	FIRE ALARM SYSTEM RELAY
	SPRINKLER FLOW SWITCH, PROVIDED BY PLUMBING CONTRACTOR
	SPRINKLER TAMPER SWITCH, PROVIDED BY PLUMBING CONTRACTOR
	FIRE SPRINKLER SYSTEM BELL (GONG), +10'-0" AFG
	COMBINATION FIRE/SMOKE DAMPER PROVIDED BY MECHANICAL CONTRACTOR
	ABOVE FINISHED FLOOR/GRADE
	AUTHORITY HAVING JURISDICTION
	BUILDING AUTOMATION SYSTEM
	ELECTRICAL CONTRACTOR
	FIRE ALARM
	GENERAL CONTRACTOR
	MECHANICAL CONTRACTOR
	NIGHT LIGHT
	NON-FUSED
	PLUMBING CONTRACTOR
	TYPICAL
	WEATHERPROOF

SYMBOLS LEGEND NOTES:
MOUNTING HEIGHTS INDICATED ARE MEASURED FROM FINISHED FLOOR TO THE CENTERLINE OF THE DEVICE UNLESS NOTED OTHERWISE.

Property

GO CAR WASH-INWOOD,
WW
INWOOD-BERKELEY COUNTY, WV
ELECTRICAL NOTES & LEGEND

Sheet Number

E0.1

BASIC ELECTRICAL

- 1. THE WORK COVERED BY DIVISION 16 CONSISTS OF FURNISHING ALL LABOR, EQUIPMENT, SUPPLIES, AND MATERIALS (EXCEPT AS OTHERWISE SPECIFIED OR SHOWN ON THE DRAWINGS) REQUIRED TO PERFORM ALL OPERATIONS NECESSARY FOR THE INSTALLATION OF COMPLETE ELECTRICAL SYSTEMS. ALL WORK SHALL BE IN STRICT ACCORDANCE WITH THE SPECIFICATIONS AND DRAWINGS.
2. COORDINATE ALL WORK WITH OTHER TRADES AND EXISTING CONDITIONS TO PREVENT CONFLICTS CAUSING UNNECESSARY EXPENSE OR DELAYS IN THE INSTALLATION OF WORK.
3. ALL WORK SHALL COMPLY WITH THE LOCALLY ADOPTED ELECTRICAL CODE AND ALL APPLICABLE LAWS, CODES, RECOMMENDATIONS, REGULATIONS, AND INTERIM AMENDMENTS...

GROUNDING

- 1. EXTENT OF ELECTRICAL GROUNDING AND BONDING WORK IS INDICATED BY DRAWINGS AND AS SPECIFIED HEREIN. GROUNDING AND BONDING WORK IS DEFINED TO ENCOMPASS SYSTEMS, CIRCUITS, AND EQUIPMENT.
2. EXCEPT AS OTHERWISE INDICATED, PROVIDE ELECTRICAL GROUNDING AND BONDING SYSTEMS INDICATED BY ASSEMBLY OF MATERIALS, INCLUDING, BUT NOT LIMITED TO, CABLES/WIRES, CONNECTORS, SOLDERLESS LUG TERMINALS, GROUNDING ELECTRODES AND PLATE ELECTRODES, BONDING JUMPER BRAID, AND ADDITIONAL ACCESSORIES NEEDED FOR A COMPLETE INSTALLATION.
3. INSTALL ELECTRICAL GROUNDING AND BONDING SYSTEMS AS INDICATED, IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPLICABLE PORTIONS OF THE BUILDING CODES, NECA'S "STANDARD OF INSTALLATION", AND IN ACCORDANCE WITH RECOGNIZED INDUSTRY PRACTICES TO ENSURE THAT PRODUCTS COMPLY WITH REQUIREMENTS.

IDENTIFICATION

- 1. ENGRAVED, PLASTIC-LAMINATED LABELS, SIGNS, AND INSTRUCTION PLATES: ENGRAVING STOCK MELAMINE PLASTIC LAMINATE, 1/16-INCH MINIMUM THICK FOR SIGNS UP TO 20 SQUARE INCHES, OR 8 INCHES IN LENGTH; 1/8-INCH THICK FOR LARGER SIZES. ENGRAVED LEGEND IN WHITE LETTERS ON BLACK FACE AND PUNCHED FOR MECHANICAL FASTENERS.
2. CABLE TIES: FUNGUS-INERT, SELF-EXTINGUISHING, ONE-PIECE, SELF-LOCKING NYLON CABLE TIES, 0.18-INCH MINIMUM WIDTH, 50-LB MINIMUM TENSILE STRENGTH, AND SUITABLE FOR A TEMPERATURE RANGE FROM MINUS 50 F TO 350 F.
3. SELF ADHESIVE, COMMERCIALY AVAILABLE ARC FLASH HAZARD LABELS. LABELS TO CONFORM TO THE ADOPTED ELECTRICAL CODE AND A.N.S.I. 2535.4.

WIRES AND CABLES

- 1. CONDUCTORS: PROVIDE SOLID CONDUCTORS FOR POWER AND LIGHTING CIRCUITS NO. 10 AWG AND SMALLER. PROVIDE STRANDED CONDUCTORS FOR SIZES NO. 8 AWG AND LARGER.
2. CONDUCTOR MATERIAL: COPPER FOR ALL WIRES AND CABLES.
3. INSULATION: PROVIDE THHN/THWN INSULATION FOR ALL CONDUCTORS NO. 14 AWG THRU NO. 10 AWG. FOR ALL OTHER SIZES PROVIDE THHN/THWN OR XHHW INSULATION AS APPROPRIATE FOR THE LOCATION WHERE INSTALLED.
4. ALUMINUM CONDUCTORS ARE NOT APPROVED OR ACCEPTABLE.
5. ALUMINUM CONDUCTORS:
A. AT THE CONTRACTOR'S OPTION, ALUMINUM CONDUCTORS WILL BE ALLOWED FOR COPPER SIZES RATED FOR 100 AMPERES AND LARGER BUT SIZE MUST BE INCREASED TO EQUAL OR EXCEED THE COPPER AMPACITY IN ACCORDANCE WITH ADOPTED ELECTRICAL CODE. RACEWAY AND PULL BOXES MUST BE INCREASED TO CONFORM TO ADOPTED ELECTRICAL CODE. ALL ALUMINUM CONDUCTORS MUST BE MADE BASED ON COMPACT STRANDED, AA-8000 SERIES ALUMINUM ALLOY MATERIAL EQUAL TO "STABILOY" ALCAN CABLE.

INSTALLATION OF WIRES AND CABLES:

- 1. ALL BRANCH CIRCUIT WIRES, FEEDER CABLES, ETC., SHALL BE CONTINUOUS FROM OUTLET TO OUTLET. NO JOINTS SHALL BE MADE EXCEPT IN OUTLET, JUNCTION OR PULL BOXES, PANELBOARD AND SWITCHBOARD GUTTERS.
2. TIGHTEN ELECTRICAL CONNECTORS AND TERMINALS, INCLUDING SCREWS AND BOLTS, IN ACCORDANCE WITH MANUFACTURER'S PUBLISHED TORQUE TIGHTENING VALUES.
3. TERMINALS ON SWITCHES AND CONVENIENCE OUTLETS SHALL NOT BE USED TO "FEED THROUGH" TO THE NEXT SWITCH OR OUTLET.
4. PANELBOARDS, ELECTRICAL CABINETS, AND ENCLOSURES
B. ELECTRICAL SWITCHGEAR AND SWITCHBOARDS
C. MOTOR STARTERS AND/OR VFDs FURNISHED BY THIS CONTRACTOR
D. DISCONNECT SWITCHES
E. CONTACTORS

Table with 2 columns: Color and Phase. Rows include BLACK (A), RED (B), BLUE (C), WHITE (NEUTRAL), GREEN (GROUND), and GREEN W/ YELLOW STRIP (ISOLATED GROUND).

IDENTIFICATION

- 1. ENGRAVED, PLASTIC-LAMINATED LABELS, SIGNS, AND INSTRUCTION PLATES: ENGRAVING STOCK MELAMINE PLASTIC LAMINATE, 1/16-INCH MINIMUM THICK FOR SIGNS UP TO 20 SQUARE INCHES, OR 8 INCHES IN LENGTH; 1/8-INCH THICK FOR LARGER SIZES. ENGRAVED LEGEND IN WHITE LETTERS ON BLACK FACE AND PUNCHED FOR MECHANICAL FASTENERS.
2. CABLE TIES: FUNGUS-INERT, SELF-EXTINGUISHING, ONE-PIECE, SELF-LOCKING NYLON CABLE TIES, 0.18-INCH MINIMUM WIDTH, 50-LB MINIMUM TENSILE STRENGTH, AND SUITABLE FOR A TEMPERATURE RANGE FROM MINUS 50 F TO 350 F.
3. SELF ADHESIVE, COMMERCIALY AVAILABLE ARC FLASH HAZARD LABELS. LABELS TO CONFORM TO THE ADOPTED ELECTRICAL CODE AND A.N.S.I. 2535.4.

RACEWAYS

- 1. THIS SECTION INCLUDES RACEWAYS FOR ELECTRICAL WIRING. TYPES OF RACEWAYS IN THIS SECTION INCLUDE THE FOLLOWING:
A. ELECTRICAL METALLIC TUBING (EMT)
B. INTERMEDIATE METAL CONDUIT (IMC)
C. FLEXIBLE METAL CONDUIT
D. LIQUID-TIGHT FLEXIBLE CONDUIT
E. RIGID METAL CONDUIT (RMC)
F. RIGID NONMETALLIC CONDUIT (PVC)
G. SURFACE RACEWAYS
H. WIREWAY
I. METAL CLAD (MC) AND ALUMINUM CLAD (AC) CABLE
2. WIREWAYS:
A. ELECTRICAL WIREWAYS SHALL BE OF TYPES, SIZES, AND NUMBER OF CHANNELS AS INDICATED. FITTINGS AND ACCESSORIES INCLUDING BUT NOT LIMITED TO COUPLINGS, OFFSETS, ELBOWS, EXPANSION JOINTS, ADAPTERS, HOLD-DOWN STRAPS, AND END CAPS SHALL MATCH AND MATE WITH WIREWAY AS REQUIRED FOR A COMPLETE SYSTEM.
3. PULL AND JUNCTION BOXES:
A. COMPLY WITH UL 50, "ELECTRICAL CABINETS AND BOXES", FOR BOXES OVER 100 CUBIC INCHES VOLUME.
4. CABINETS:
A. COMPLY WITH UL 50, "ELECTRICAL CABINETS AND BOXES". SHEET STEEL, NEMA CLASS EXCEPT AS OTHERWISE INDICATED.

CABINET, BOXES AND FITTINGS

- 1. THIS SECTION INCLUDES CABINETS, BOXES, AND FITTINGS FOR ELECTRICAL INSTALLATIONS AND CERTAIN TYPES OF ELECTRICAL FITTINGS NOT COVERED IN OTHER SECTIONS.
2. METAL OUTLET, DEVICE, AND SMALL WIRING BOXES:
A. GENERAL: CONFORM TO UL 514A, "METALLIC OUTLET BOXES, ELECTRICAL," AND UL 514B, "FITTINGS FOR CONDUIT AND OUTLET BOXES."
3. PULL AND JUNCTION BOXES:
A. COMPLY WITH UL 50, "ELECTRICAL CABINETS AND BOXES", FOR BOXES OVER 100 CUBIC INCHES VOLUME.
4. CABINETS:
A. COMPLY WITH UL 50, "ELECTRICAL CABINETS AND BOXES". SHEET STEEL, NEMA CLASS EXCEPT AS OTHERWISE INDICATED.
5. STEEL ENCLOSURES WITH HINGED DOORS:
A. COMPLY WITH UL 50, "CABINETS AND ENCLOSURES" AND NEMA ICS 6, "ENCLOSURES FOR INDUSTRIAL CONTROLS AND SYSTEMS".

WIRING DEVICES

- THIS SECTION INCLUDES THE FOLLOWING:
 - RECEPTACLES
 - LIGHTING AND EQUIPMENT SWITCHES
 - WALL PLATES
 - FLOOR SERVICE OUTLETS
 - OCCUPANCY SENSORS
 - MANUAL DIMMERS
- MANUFACTURERS: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCTS BY ONE OF THE FOLLOWING:
 - WIRING DEVICES & ACCESSORIES:
 - COPPER WIRING DEVICES
 - CROUSE-HINDS CO.
 - HUBBELL INC.
 - LEVITON
 - PASS AND SEYMOUR INC.
 - FLOOR BOXES:
 - AMERICAN ELECTRIC, STEEL CITY
 - WALKER / WIREMOLD COMPANY
 - RACO, INC. HUBBELL INC.
 - RACEWAY COMPONENTS, INC.
 - DIMMERS:
 - HUBBELL INC.
 - LEVITON LIGHTING CONTROLS
 - LUTRON LIGHTING
 - OCCUPANCY SENSOR LIGHTING CONTROL:
 - HUBBELL INC.
 - LEVITON MANUFACTURING INC.
 - WATT STOPPER INC.
 - SENSOR SWITCH
 - GREENGATE
- WIRING DEVICES:
 - PROVIDE WIRING DEVICES, IN TYPES, CHARACTERISTICS, GRADES, COLORS, AND ELECTRICAL RATINGS FOR APPLICATIONS INDICATED WHICH ARE UL LISTED AND WHICH COMPLY WITH NEMA MD 1 AND OTHER APPLICABLE UL AND NEMA STANDARDS. ALL DEVICES TO BE SPECIFICATION GRADE (HEAVY DUTY U.L. GRADE), WITH GREEN HEXAGONAL EQUIPMENT GROUND SCREW, METAL PLASTER EARS AND SIDE TERMINAL SCREWS FOR BACK AND SIDE WIRING.
 - ALL WIRING DEVICES ARE TO BE PROVIDED BY THE SAME MANUFACTURER UNLESS NOTED OTHERWISE.
 - ALL WIRING DEVICES AND COVERPLATES SHALL BE:
 - WHITE
 - WHITE - WHERE INSTALLED IN WHITE CEILINGS.
 - BLACK - WHERE INSTALLED IN DARK CEILINGS.
 - ORANGE - WHERE SUPPLYING A UPS CIRCUIT. (DEVICE ONLY, COVERPLATE SHALL BE AS ABOVE).
 - RECEPTACLES:
 - DUPLEX RECEPTACLE, 15 AMP, 125 VOLT, 2-POLE, 3-WIRE, GROUNDING TYPE WITH NEMA CONFIGURATION 5-15R, MEETS FEDERAL SPEC. WC-596-F. LEVITON #5252.
 - SINGLE RECEPTACLE, 20 AMP, 125 VOLT, 2-POLE, 3-WIRE, GROUNDING TYPE WITH NEMA CONFIGURATION 5-20R, MEETS FEDERAL SPEC. WC-596-F. LEVITON #5351.
 - DUPLEX RECEPTACLE, 20 AMP, 125 VOLT, 2-POLE, 3-WIRE, GROUNDING TYPE WITH NEMA CONFIGURATION 5-20R, MEETS FEDERAL SPEC. WC-596-F. LEVITON #5352.
 - GROUND FAULT INTERRUPTER RECEPTACLE, 20 AMP, 125 VOLT, 2-POLE, 3-WIRE, GROUNDING TYPE WITH NEMA CONFIGURATION 5-20R. UL943 APPROVED, SELF-TESTING, SOLID STATE GROUND FAULT SENSING LEVEL WITH 5 MILLIAMPERES GROUND FAULT TRIP LEVEL. LED INDICATOR LIGHT WITH TEST/RESET BUTTONS THAT MATCH THE COLOR OF THE FACE. LEVITON #G5362-W1*.
 - USB RECEPTACLE, 20A, 125V, 2-POLE, 3-WIRE, GROUNDING TYPE WITH NEMA CONFIGURATION 5-20R, (2) VERTICAL USB PORTS WITH 3.6A CHARGING CAPACITY (MINIMUM), MEETS FEDERAL SPEC. WC-596-F. LEVITON #F5832
 - WHERE SHOWN AS A QUAD RECEPTACLE ON PLANS, PROVIDE (2) USB RECEPTACLES AS SPECIFIED ABOVE.
 - WEATHERPROOF RECEPTACLE SHALL BE A GROUND-FAULT INTERRUPTER WITH THOMAS & BETTS JOXSVY, DIE-CAST ALUMINUM "SMALL" COVER PLATE, LOCATE BOX VERTICAL IN WALL. PLATE TO BE LISTED AND LABELED "SUITABLE FOR WET LOCATIONS WHILE IN USE."
 - ISOLATED GROUND DUPLEX RECEPTACLE, 20 AMP, 125 VOLT, 2-POLE, 3-WIRE, FACE WITH ORANGE TRIANGLE, GROUND SCREW ISOLATED FROM MOUNTING YOKE, NEMA CONFIGURATION 5-20RIG. LEVITON #5362-IG.
 - CONTROLLED DUPLEX RECEPTACLE, 20 AMP, 125 VOLT, 2-POLE, 3-WIRE, GROUNDING TYPE WITH NEMA CONFIGURATION 5-20R, PERMANENTLY LABELED WITH CONTROLLED SYMBOL, MEETS FEDERAL SPEC. WC-596-F. LEVITON #5362-2.
 - WHERE SHOWN AS A QUAD RECEPTACLE ON PLANS, PROVIDE (1) CONTROLLED RECEPTACLE AND (1) DUPLEX RECEPTACLE AS SPECIFIED ABOVE.
 - HEAVY DUTY RECEPTACLES SHALL BE OF THE SAME MANUFACTURER AS THE CONVENIENCE OUTLETS AND HAVE THE RATINGS AND CHARACTERISTICS (VOLTAGE, AMPS, POLES, WIRES) AS SHOWN ON DRAWINGS.
 - SWITCHES:
 - TOGGLE TYPE SWITCH, 20 AMP, 120/277 VOLT AC SINGLE-POLE, QUITE TYPE, WITH MOUNTING YOKE INSULATED FROM MECHANISM, EQUIPPED WITH PLASTER EARS, SIDE-WIRED SCREW TERMINALS, MEETS FEDERAL SPEC WS-896. LEVITON #1121-2.
 - DOUBLE-POLE, 3-WAY, AND 4-WAY SWITCHES SHALL BE OF THE SAME MAKE AS FOR SINGLE-POLE.
 - KEY TYPE SWITCH, 20 AMP, 120/277 VOLT AC SINGLE-POLE, WITH MOUNTING YOKE INSULATED FROM MECHANISM, EQUIPPED WITH PLASTER EARS, SIDE-WIRED SCREW TERMINALS, POLISHED METAL TOP AND PROVIDE WITH ONE STEEL KEY. LEVITON #1121-2L.
 - DOUBLE-POLE, 3-WAY, AND 4-WAY SWITCHES SHALL BE OF THE SAME MAKE AS FOR SINGLE-POLE.
 - WHEN A LIGHTED HANDLE IS INDICATED WITH SWITCHING DEVICE, PROVIDE SWITCH DEVICE WITH 1/25 WATT NEON PILOT INTEGRAL WITH TOGGLE HANDLE, RATED 120/277 VOLT. GLOWS WHEN SWITCH IS "OFF". PASS & SEYMOUR #20AC1-CSL.
 - WHEN A PILOT LIGHT IS INDICATED WITH SWITCHING DEVICE, PROVIDE SWITCH DEVICE WITH 1/25 WATT NEON PILOT INTEGRAL WITH TOGGLE HANDLE, RATED 120/277 VOLT. GLOWS WHEN SWITCH IS "ON". PASS & SEYMOUR #20AC1-RPL.
 - FLOOR RECEPTACLES:
 - TYPE 'A': HUBBELL #B-2436, RECTANGULAR SINGLE-GANG, WATER-TIGHT BOX WITH ONE S-3825 DUPLEX FLAP COVER. BOX COVER PLATE SHALL BE BRASS. COVER TO BE PROVIDED WITH BRASS CARPET FLANGE FOR FLUSH INSTALLATION IN LINOLEUM, WOOD OR CARPET FLOORS. EACH FLOOR OUTLET SHALL BE COMPLETE WITH ONE 20 AMP, 125 VOLT DUPLEX BROWN RECEPTACLE AS SPECIFIED UNDER "RECEPTACLES".
 - TYPE 'B': HUBBELL #B-4233, RECTANGULAR DOUBLE-GANG, FULLY ADJUSTABLE, WATER-TIGHT BOX WITH ONE S-3825 DUPLEX FLAP COVER COMPLETE WITH ONE 20 AMP, 125 VOLT DUPLEX BROWN RECEPTACLE AS SPECIFIED UNDER "RECEPTACLES". ALSO PROVIDE ONE S-2625 COVER PLATE WITH ONE S-3067 SPLIT NOZZLE FOR PROTECTION OF TELEPHONE/COMPUTER CABLES. BOX COVER PLATES SHALL BE BRASS. COVER TO BE PROVIDED WITH BRASS CARPET FLANGE FOR FLUSH INSTALLATION IN LINOLEUM, WOOD OR CARPET FLOORS.
 - TYPE 'C': HUBBELL #B-2436, RECTANGULAR SINGLE-GANG BOX, BRASS PLATE #S2425 WITH 3/4" PLUG OPENING FOR CONNECTION OF FLEXIBLE CONDUIT FROM EQUIPMENT. COVER TO BE PROVIDED WITH BRASS CARPET FLANGE FOR FLUSH INSTALLATION IN LINOLEUM, WOOD OR CARPET FLOORS.

WIRING DEVICES

- WALL PLATES: SINGLE AND COMBINATION, OF TYPES, SIZES, AND WITH GANGING AND CUTOUPS AS INDICATED. PROVIDE PLATES WHICH MATE WITH WIRING DEVICES TO WHICH ATTACHED. PROVIDE METAL SCREWS FOR SECURING PLATES TO DEVICES WITH SCREW HEADS TO MATCH FINISH OF PLATES. PROVIDE WALL PLATES WITH ENGRAVED LEGEND WHERE INDICATED. CONFORM TO REQUIREMENTS OF SECTION "ELECTRICAL IDENTIFICATION."
- OCCUPANCY SENSOR LIGHTING CONTROL:
 - WALL MOUNTED OCCUPANCY SENSOR TO BE PASSIVE INFRARED COVERING 1200 (OR 900) SQUARE FEET, RATED FOR 120/277 VOLT, 1500 WATTS MAXIMUM LOAD OF INCANDESCENT OR FLUORESCENT LIGHT. SENSOR TO HAVE 180° FIELD OF VIEW, OFF/AUTO/ON SLIDE SWITCH, ADJUSTABLE TIME-OUT FROM 1 TO 20 MINUTES, AND LED MOVEMENT INDICATOR PILOT. SENSOR TO BE MOUNTED IN A SINGLE-GANG WALL BOX AT SAME ELEVATION AS STANDARD WALL SWITCHES.
 - WATT STOPPER #PW-100 SINGLE REALY (OR #PW-200 DUAL REALY).
 - CEILING MOUNTED OCCUPANCY SENSOR TO BE DUAL TECHNOLOGY WITH ULTRASONIC & PASSIVE INFRARED TYPE SENSORS. SENSORS TO HAVE TWO-WAY OR ONE-WAY DISTRIBUTION DEPENDING ON MOUNTING LOCATION CAPABLE OF ADJUSTING THE SENSITIVITY AND LENGTH OF OPERATION BASED ON PAST ACTIVITY LEVEL OF THE AREA'S OCCUPANTS. CUSTOM PERFORMANCE CONTROLS TO BE LOCATED BEHIND THE SENSOR LENS FOR FIELD MODIFICATION OF SENSOR DESIGN. UNIT TO BE MOUNTED TO RECESSED JUNCTION BOX.
 - WATT STOPPER #DT-355, 800W @ 120V (1200W @ 277V)
- MANUAL DIMMERS:
 - PROVIDE AND INSTALL AC DIMMER CONTROLS FOR LIGHTING FIXTURES; WATTAGE AS INDICATED BELOW, 120 VOLT, 60 HERTZ, WITH PRESET SLIDE CONTROLS AND PUSHBUTTON FOR ON/OFF CONTROLS, SINGLE-POLE:
 - ID1 = 1000 WATTS, LEVITON #P110-1LX (120/277V INCANDESCENT)
 - D1 = 1200/1500 VA, LEVITON #P710-LFZ (120/277V LED)
 - L2 = 400 VA, LEVITON #PE04-1LX (ELECTRONIC LOW VOLTAGE)
 - L3 = 1000 VA, LEVITON #IPM10-1LX (MAGNETIC LOW VOLTAGE)
 - F1 = 1200/1500 VA, LEVITON #IP710-DLX (120/277V FLUORESCENT 0-10V)
 - F2 = 1000 VA, LEVITON #IPX10-10 (120V FLUORESCENT LINE VOLTAGE)
 - F3 = 1200 VA, LEVITON #IPX12-70 (277V FLUORESCENT LINE VOLTAGE)
- INSTALLATION OF WIRING DEVICES AND ACCESSORIES:
 - GROUPS OF SWITCHES OR SWITCH AND OUTLET COMBINATIONS SHALL BE MOUNTED UNDER ONE COVER PLATE. COVER PLATES SHALL FIT THE DEVICES SECURELY AND SHALL COVER THE WALL OPENING COMPLETELY TO PROVIDE A NEAT AND FINISHED APPEARANCE FLUSH WITH SURROUNDING SURFACES.
 - TERMINALS ON ALL WIRING DEVICES SHALL NOT BE USED TO FEED-THROUGH TO THE NEXT DEVICES.
 - INSTALL WALL-MOUNTED RECEPTACLES WITH GROUND SLOT UP.
 - RECEPTACLE MOUNTED ABOVE COUNTER-TOP TO BE INSTALLED HORIZONTAL, WITH LONG DIMENSION PARALLEL TO FLOOR AND COUNTER-TOP.

FUSES

- MANUFACTURER: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCTS OF ONE OF THE FOLLOWING (FOR EACH TYPE AND RATING OF OVERCURRENT PROTECTIVE DEVICE):
 - BUSSMANN DIV, MCGRAW_EDISON CO.
 - FERRAZ SHAWMUT, INC.
 - LITTELFUSE, INC.
- EXCEPT AS OTHERWISE INDICATED, PROVIDE FUSES OF TYPES, SIZES, RATINGS, AND AVERAGE TIME/CURRENT AND PEAK LET-THROUGH CURRENT CHARACTERISTICS INDICATED, WHICH COMPLY WITH MANUFACTURER'S STANDARD DESIGN, MATERIALS, AND CONSTRUCTION IN ACCORDANCE WITH PUBLISHED PRODUCT INFORMATION, AND WITH INDUSTRY STANDARDS AND CONFIGURATIONS. ALL FUSES TO BE FOR USE WITH FUSE REJECTION CLIPS.
- ALL FUSES FOR THIS PROJECT SHALL BE OF THE SAME MANUFACTURER TO INSURE SELECTIVE COORDINATION.
- EXCEPT WHERE NOTED OTHERWISE, THREE (3) SPARE FUSES OF EACH SIZE INSTALLED SHALL BE PROVIDED TO THE OWNER.
- INSTALL FUSES WITH MANUFACTURER'S NAMETAG FACING OUTWARD.
- SERVICE ENTRANCE AND FEEDER CIRCUITS 601 AMPERES AND LARGER, FUSES SHALL BE BOLT-ON U.L. LISTED CLASS L, CURRENT-LIMITING WITH 200,000 AMPERES R.M.S. SYMMETRICAL INTERRUPTING RATING.
- FEEDER CIRCUITS, EXCEPT MOTOR CIRCUITS, 600 AMPERES AND SMALLER SHALL BE PLUG-IN CARTRIDGE U.L. CLASS RK-1, CURRENT-LIMITING WITH 200,000 AMPERES R.M.S. SYMMETRICAL INTERRUPTING RATING.
- MOTOR, TRANSFORMERS, AND INDUCTIVE TYPE CIRCUITS 600 AMPERES AND SMALLER SHALL BE PLUG-IN CARTRIDGE U.L. CLASS RK-5 DUAL-ELEMENT WITH TIME DELAY. THEY SHALL ALSO HAVE CURRENT-LIMITING LINKS AND 200,000 AMPERES INTERRUPTING RATING. FUSE REDUCERS SHALL BE USED WHERE SWITCH FUSE CLIPS ARE SPACED LARGER THAN FUSE SIZE SHOWN ON DRAWING.
- PLUG FUSES FOR INDIVIDUAL MOTOR PROTECTION SHALL BE BUSSMANN FUSTAT, DUAL-ELEMENT, 10,000 AMPERES R.M.S. SYMMETRICAL INTERRUPTING RATING TYPE "S" WITH FUSTAT ADAPTER SIZED FOR PLUG-FUSE INSTALLED. SIZE OF FUSE TO BE ACCORDING TO SPECIFICATIONS FOR "DISCONNECT SWITCHES".

SUPPORTING DEVICES

- THIS SECTION INCLUDES SECURE SUPPORT FROM THE BUILDING STRUCTURE FOR ELECTRICAL ITEMS BY MEANS OF HANGERS, SUPPORTS, ANCHORS, SLEEVES, INSERTS, SEALS, AND ASSOCIATED FASTENINGS.
- COATING: SUPPORTS, SUPPORT HARDWARE, AND FASTENERS SHALL BE PROTECTED WITH ZINC COATING OR WITH TREATMENT OF EQUIVALENT CORROSION RESISTANCE USING APPROVED ALTERNATIVE TREATMENT, FINISH, OR INHERENT MATERIAL CHARACTERISTIC. PRODUCTS FOR USE OUTDOORS SHALL BE HOT-DIP GALVANIZED.
- INSTALL SUPPORTING DEVICES TO FASTEN ELECTRICAL COMPONENTS SECURELY AND PERMANENTLY IN ACCORDANCE WITH MANUFACTURER'S REQUIREMENTS.
- SUPPORT INDIVIDUAL HORIZONTAL RACEWAYS BY SEPARATE PIPE HANGERS. SPRING STEEL FASTENERS MAY BE USED IN LIEU OF HANGERS ONLY FOR 3/4-INCH AND SMALLER RACEWAYS SERVING LIGHTING AND RECEPTACLE BRANCH CIRCUITS ABOVE SUSPENDED CEILINGS ONLY. FOR HANGER RODS WITH SPRING STEEL FASTENERS, USE 1/4-INCH-DIAMETER OR LARGER THREADED STEEL. USE SPRING STEEL FASTENERS THAT ARE SPECIFICALLY DESIGNED FOR SUPPORTING SINGLE CONDUITS OR TUBING. CONDUITS ABOVE LAY-IN CEILING SYSTEM SHALL NOT BE SUPPORTED FROM CEILING SUSPENSION WIRES.
- INSTALL INDIVIDUAL AND MULTIPLE (TRAPEZE) RACEWAY HANGERS AND RISER CLAMPS AS NECESSARY TO SUPPORT RACEWAYS. PROVIDE U-BOLTS, CLAMPS, ATTACHMENTS AND OTHER HARDWARE NECESSARY FOR HANGER ASSEMBLY AND FOR SECURING HANGER RODS AND CONDUITS.
- SUPPORT PARALLEL RUNS OF HORIZONTAL RACEWAYS TOGETHER ON TRAPEZE-TYPE HANGERS
- DO NOT CUT HOLES IN REINFORCED CONCRETE BEAMS OR CUT REINFORCING BARS IN CONCRETE WITH OUT WRITTEN APPROVAL OF STRUCTURAL ENGINEER.
- UNLESS OTHERWISE INDICATED, FASTEN ELECTRICAL ITEMS AND THEIR SUPPORTING HARDWARE SECURELY TO THE BUILDING STRUCTURE, INCLUDING BUT NOT LIMITED TO CONDUITS, RACEWAYS, CABLES, CABLE TRAYS, BUSWAYS, CABINETS, PANELBOARDS, TRANSFORMERS, BOXES, DISCONNECT SWITCHES, AND CONTROL COMPONENTS.

DISCONNECTS, CONTACTORS

- MANUFACTURERS: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCTS BY ONE OF THE FOLLOWING:
 - GENERAL ELECTRIC CO.
 - SQUARE D COMPANY.
 - EATON CORPORATION
 - SIEMENS, I.T.E.
 - ALLEN-BRADLEY CO.
 - FURNAS CO.
- TEMPERATURE RATINGS: ALL CONDUCTOR TERMINALS AND EQUIPMENT ENCLOSURES TO BE U.L. LISTED FOR USE WITH MINIMUM 75C RATED CONDUCTORS.
- DISCONNECT SWITCHES:
 - PROVIDE CIRCUIT AND MOTOR DISCONNECT SWITCHES OF TYPES, SIZES AND ELECTRICAL CHARACTERISTICS INDICATED ON DRAWING. FUSIBLE OR NON-FUSED TYPE, RATED 250 OR 600 VOLTS, 60 HZ, 2- OR 3-POLES, SOLID NEUTRAL, AND INCORPORATING QUICK-MAKE, QUICK-BREAK TYPE SWITCHES; CONSTRUCT SO THAT SWITCH BLADES ARE VISIBLE IN OFF POSITION WITH DOOR OPEN. SWITCH SHALL HAVE A DUAL COVER INTERLOCK TO PREVENT UNAUTHORIZED OPENING OF THE SWITCH DOOR WHEN HANDLE IS IN THE "ON" POSITION, AND TO PREVENT CLOSING OF THE SWITCH MECHANISM WITH THE DOOR OPEN. EQUIP WITH OPERATING HANDLE WHICH IS INTEGRAL PART OF ENCLOSURE BASE AND WHOSE POSITION IS EASILY RECOGNIZABLE, AND IS PADLOCKABLE IN OFF POSITION; CONSTRUCT CURRENT CARRYING PARTS OF HIGH-CONDUCTIVITY COPPER, WITH SILVER-TUNGSTEN TYPE SWITCH CONTACTS, AND POSITIVE PRESSURE TYPE REINFORCED FUSE CLIPS. PROVIDE SWITCH IN NEMA 1 OR NEMA TYPE 3R ENCLOSURE AS INDICATED OR REQUIRED. INSTALL ENGRAVED PLASTIC PLATE AS TO WHAT EACH SWITCH CONTROLS.
 - EQUIPMENT REQUIRING A DISCONNECTING MEANS, RATED FOR 120 OR 208 VOLT SINGLE PHASE, UP TO 30 AMPERES MAY BE PROVIDED WITH A SNAP-FUSED TYPE TOGGLE DEVICE AT THE EQUIPMENT. THE DEVICE IS TO HAVE AN AMPERE AND VOLTAGE RATING EQUAL TO OR GREATER THAN THE BRANCH CIRCUIT FEEDING THE EQUIPMENT. IF EQUIPMENT IS MOTOR RELATED, THEN THE SWITCH MUST BE HORSEPOWER RATED. REFER TO SECTION 16140 FOR MINIMUM SPECIFICATIONS FOR TOGGLE SWITCHES. SWITCHES LOCATED OUTDOORS OR IN COOLER/FREEZER APPLICATIONS ARE TO BE MOUNTED IN A DIE-CAST ALUMINUM DEVICE BOX WITH GASKETED WEATHERPROOF COVER PLATE.
- RELAYS AND CONTACTORS:
 - GENERAL POWER PURPOSE RELAYS, FOR CONTROL OF MISCELLANEOUS MOTORS, TO BE PROVIDED AND INSTALLED WITH NUMBER OF POLES AND COIL VOLTAGE AS SHOWN ON DRAWINGS. RELAY TO BE HORSEPOWER RATED FOR THE MOTOR LOAD TO WHICH IT CONTROLS. RELAY TO BE MOUNTED IN A NEMA TYPE 1 ENCLOSURE.
 - LIGHTING CONTACTORS TO BE PROVIDED AND INSTALLED WITH THE NUMBER OF POLES, COIL VOLTAGE, AND LOAD CONTACT RATINGS AS SHOWN ON DRAWINGS. CONTACTORS TO BE PROVIDED WITH SILVER ALLOY DOUBLE BREAK CONTACTS RATED FOR TUNGSTEN AND BALLAST LIGHTING LOADS. CONTACTORS TO BE CONVERTIBLE WITH NORMALLY OPEN AND NORMALLY CLOSED INDICATORS. RELAY TO BE MOUNTED IN A NEMA TYPE 1 ENCLOSURE.
- INSTALLATION OF DISCONNECTS AND STARTERS:
 - SURFACE MOUNT ON WALLS OR COLUMNS APPROXIMATELY 5'-0" TO CENTERLINE ABOVE THE FLOOR WHERE POSSIBLE.
 - DISCONNECT SWITCHES MOUNTED ON ROOFTOP AIR CONDITIONING UNITS TO BE CALKED BETWEEN SWITCH AND UNIT TO PROVIDE WEATHERPROOF SEAL. ELECTRICAL CONTRACTOR TO VERIFY EXACT MOUNTING LOCATION ON UNIT SO AS NOT TO COVER UP ANY REMOVABLE PANELS.
 - WHEN RELAYS OR CONTACTORS ARE INDICATED TO BE LOCATED ABOVE THE CEILING, THE EQUIPMENT IS TO BE READILY ACCESSIBLE AND SOUND INSULATED FROM THE MOUNTING SUPPORTS.


PANELBOARDS

- MANUFACTURERS: SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PANELBOARD PRODUCTS OF ONE OF THE FOLLOWING (FOR EACH TYPE AND RATING OF PANELBOARD AND ENCLOSURE):
 - GENERAL ELECTRIC COMPANY
 - SQUARE D COMPANY
 - EATON CORPORATION
 - SIEMENS, I.T.E.
- POWER DISTRIBUTION PANELS: PROVIDE DEAD-FRONT SAFETY-TYPE DISTRIBUTION PANELBOARDS RATED 208/120, 3-PHASE, 4-WIRE. SHORT CIRCUIT RATING OF PANEL AND DEVICES TO BE 22,000 RMS MINIMUM UNLESS NOTED OTHERWISE ON THE DRAWINGS. PANELBOARDS SWITCHING AND PROTECTIVE DEVICES IN SOLDERLESS PRESSURE-TYPE LINE SIDE CONNECTORS APPROVED FOR COPPER CONDUCTORS.
- 120/208 VOLT LIGHTING AND APPLIANCE PANELBOARDS: PROVIDE DEAD-FRONT SAFETY TYPE LIGHTING AND APPLIANCE PANELBOARDS AS INDICATED, WITH SWITCHING AND PROTECTIVE DEVICES IN QUANTITIES, RATINGS, TYPES AND ARRANGEMENTS SHOWN, WITH ANTI-TURN SOLDERLESS PRESSURE TYPE LUG CONNECTORS. APPROVED FOR USE WITH COPPER CONDUCTORS; CONSTRUCT UNIT FOR CONNECTING FEEDERS TO PANEL; EQUIP WITH COPPER, COPPER PLATED OR ALUMINUM BUS BARS, FULL-SIZED NEUTRAL BAR, WITH BOLT-IN TYPE HEAVY-DUTY, QUICK-MAKE, QUICK-BREAK, SINGLE-POLE CIRCUIT-BREAKERS, WITH TOGGLE HANDLES THAT INDICATE WHEN TRIPPED. PROVIDE SUITABLE LUGS ON NEUTRAL BUS FOR EACH OUTGOING FEEDER REQUIRED; AND PROVIDE BARE UNINSULATED GROUNDING BARS SUITABLE FOR BOLTING TO ENCLOSURES. SELECT ENCLOSURES FABRICATED BY SAME MANUFACTURER AS PANELBOARDS, WHICH MATE AND MATCH PROPERLY WITH PANELBOARDS. MINIMUM INTERRUPTING CAPACITY OF MANUFACTURED PANELBOARDS TO BE 10,000 A.I.C. UNLESS NOTED OTHERWISE ON THE DRAWINGS.
- MOLDED-CASE CIRCUIT BREAKERS: PROVIDE FACTORY ASSEMBLED, MOLDED CASE CIRCUIT BREAKERS OF FRAME SIZE INDICATED. PROVIDE BREAKERS WITH PERMANENT THERMAL AND INSTANTANEOUS MAGNETIC TRIPS IN EACH POLE AND AMPERE RATING AS INDICATED. CONSTRUCT WITH OVER CENTER, TRIP-FREE, TOGGLE TYPE OPERATING MECHANISMS WITH QUICK-MAKE, QUICK-BREAK ACTION AND POSITIVE HANDLE INDICATION. CONSTRUCT BREAKERS FOR MOUNTING AND OPERATING IN ANY PHYSICAL POSITION AND OPERATING IN AN AMBIENT TEMPERATURE OF 40C. PROVIDE BREAKERS WITH MECHANICAL SCREW TYPE REMOVABLE CONNECTOR LUGS, ALCU RATED. ALL BREAKERS TO BE BOLT-IN TYPE CONSTRUCTION. ALL BREAKERS TO BE UL489 LISTED.
 - ALL SINGLE POLE BREAKERS TO BE RATED FOR "SWITCHING DUTY" (SWD) AND FOR OPERATION ON FLUORESCENT LIGHTING SOURCES.
 - ALL CIRCUIT BREAKERS PROTECTING HIGH INTENSITY DISCHARGE (HID) LIGHTING TO BE RATED AND LABELED "HID" FOR OPERATION ON H.I.D. LIGHTING SOURCES
 - CIRCUIT BREAKERS USED ON HEATING, AIR CONDITIONING, OR REFRIGERATION EQUIPMENT SHALL BE TYPE "HACR" AND U.L. LISTED FOR SUCH USE.
- PANELBOARD MANUFACTURER TO PROVIDE A COMPLETE "ARC FLASH STUDY". ALL SUBMITTALS WILL BE REJECTED UNLESS THIS STUDY IS PROVIDED AT THE TIME OF SHOP DRAWING REVIEW.

GO CAR WASH-INWOOD,
WV
INWOOD-BERKELEY COUNTY, WV
ELECTRICAL SPECIFICATIONS

Sheet Number

E0.3



1 ELECTRICAL LIGHTING PLAN
1/8" = 1'-0"


LEGEND	TAG	DESCRIPTION	MANUFACTURER	CATALOG NUMBER	QUANTITY	WATTAGE
—	A/AEM	48" SUSPENDED LED VAPOR TIGHT	ENVOY LIGHTING	EBVTPLED-40-4KMV-ET-(BLEDEM-CP-1600-W/EM DRIVER	22	40
○	B	NOT USED	-	-	-	-
□	C	48" SUSPENDED LED VAPOR TIGHT	ENVOY LIGHTING	EWPA-3L-4K	12	23
⊞	D	24"X24" RECESSED LED FIXTURE	ENVOY LIGHTING	EBLEDPNL2X2-40L-4K-PRM	02	30
⊞	E	24"X48" RECESSED LED FIXTURE	ENVOY LIGHTING	EBLEDPNL2X2-50L-4K-PRM	05	40
EM	EM	EMRGNCY EGRESS FIXTURE W/ BACKUP	-	-	-	-
EXIT	EXIT	EMRGNCY EXIT UNIT-DUAL HEAD -INDOOR	LIGHTALARMS	UQLXN500-RN-2LED-R	-	-
E/EXIT	E/EXIT	EMRGNCY BATTERY UNIT-DUAL HEAD -OUTDOOR	LIGHTALARMS	ELF652D/LED WP	-	-

LIGHTING PLAN KEYED NOTES: #

- CONNECT ALL EMERGENCY EGRESS AND NIGHT LIGHTING FIXTURES TO THE NEAREST LIGHTING BRANCH CIRCUIT AHEAD OF ALL SWITCHING AND CONTROLS PER STATE AND LOCAL CODES.
- WEATHER PROOF EXTERIOR EMERGENCY LIGHTS. COORDINATE EXACT LOCATION WITH ARCHITECT/OWNER.
- LIGHTING SWITCH BANK IN WEATHERPROOF COVER FOR SPACE. COORDINATE FINAL LOCATION WITH ARCHITECT/OWNER. PROVIDE CIRCUIT AND CONTROL AS INDICATED.
- PROVIDE TIME CLOCK AND TIME CLOCK MANUAL OVERRIDE SWITCH, FOR EXTERIOR LIGHTING CONTROL.
- PROVIDE WALL MOUNTED OCCUPANCY SENSOR WITH SWITCH.
- PROVIDE CEILING MOUNTED OCCUPANCY SENSOR FOR LIGHTING CONTROL.
- PROVIDE CONDUIT AND CIRCUIT FROM PANEL TO SIGNAGE AT ROOF. COORDINATE WITH VENDOR FOR EXACT POWER REQUIREMENT.
- PROVIDE TWO 4' LED UTILITY STRIP LIGHTS WITH BODY AND COVER FOR LED'S 120V, 30W, 4000K. MOUNT AT AHU IN ATTIC SPACE TO PROVIDE MAINTENANCE LIGHT AS WELL AS ATTIC LIGHTING. PROVIDE SWITCH ADJACENT TO ENTRANCE HATCH AS DIRECT BY OWNER.

LUMINAIRE SCHEDULE GENERAL NOTES:

- VERIFY ALL LUMINAIRE COLORS, TRIMS, LENGTHS, ETC. WITH THE ARCHITECT PRIOR TO PLACING FINAL PURCHASE ORDERS. SUBMISSION PF SHOP DRAWINGS WILL BE INTERPRETED AS HAVING BEEN COORDINATED WITH THE ARCHITECTURAL DETAILS.
- PROVIDE ALL LENGTHS, FEEDS, ACCESSORIES, CONNECTORS, WIRING, POWER SUPPLIES, DRIVERS ETC. FOR A COMPLETE INSTALLATION. THE E.C. SHALL VERIFY THE COMPLETE BILL OF MATERIAL WITH MANUFACTURER'S REPRESENTATIVE AND ENSURE ALL EQUIPMENT ARE INCLUDED IN BID PRICE. COORDINATE INSTALLATION WITH ARCHITECTURAL DETAILS.
- VERIFY FINAL LUMINAIRE LOCATIONS WITH OTHER CEILING MOUNTED EQUIPMENTS SUCH AS DIFFUSER WITH ARCHITECTURAL REFLECTED CEILING PLANS.
- VERIFY EXACT MOUNTING HEIGHT AND LOCATIONS OF ALL WALL MOUNTED LUMINAIRE WITH ARCHITECTURAL PLANS AND ELEVATIONS PRIOR TO ROUGH-IN
- ANY PROPOSED ALTERNATE LUMINAIRES SHALL BE APPROVED BY THE ARCHITECT PRIOR TO FINAL BID PRICING.
- SHOULD THE CONTRACTOR PROPOSE TO FURNISH MATERIALS, EQUIPMENT AND DEVICES OTHER THAN THOSE SPECIFIED AND LISTED, THE CONTRACTOR SHALL SUBMIT A WRITTEN REQUEST FOR SUBSTITUTIONS, TO THE ENGINEERS AT LEAST TEN (10) BUSINESS DAYS PRIOR TO BID OPENING. THE REQUEST SHALL BE AN ALTERNATE TO THE ORIGINAL BID AND SHALL INCLUDE A COMPLETE SPECIFICATIONS CUTSHEET SUBMITTAL AS OUTLINED IN THE SPECIFICATIONS, COMPLETE WITH DESCRIPTIVE (MANUFACTURER, BRAND NAME, CATALOG NUMBER, ETC.) AND TECHNICAL DATA FOR ALL ITEMS. INDICATE ANY ADDITIONS OR DEDUCTIONS TO THE CONTRACT PRICE WITH THE SUBSTITUTION SUBMITTAL AND ON THE BID FORM.
- ALL FIXTURES INDICATED AS EMERGENCY SHALL BE PROVIDED WITH 90-MINUTE BATTERY PACK AND ALL FLORECENT FIXTURES INDICATED AS EMERGENCY SHALL BE PROVIDED WITH 1300LUMENS, 90MINUTE BATTERY PACK.
- PROVIDE SHATTER-RESISTANT LAMPS OR PROVIDE CLEAR LENSES ON ALL FIXTURES LOCATED ABOVE ALL KITCHEN AREA.
- VERIFY FINAL SELECTION OF LIGHT FIXTURES WITH ARCHITECT.



2 ELECTRICAL FLOOR POWER PLAN
1/8" = 1'-0"

LEGEND	DESCRIPTION
ES	EMERGENCY STOP BUTTON
E	ELECTRICAL EQUIPMENT CONNECTIONS AS NOTED, SEE VFD REQUIREMENTS.
SW	SWITCHES AND CONTROL
—	ELECTRICAL PANELS
MCC	MOTOR CONTROL CENTER
M	ELECTRIC MOTOR
M/WP	AC OUTDOOR UNIT
WP/GFCI	WEATHER PROOF/ GROUND FAULT CIRCUIT INTERRUPTER

POWER PLAN KEYED NOTES: #


- EXHAUST FAN IN THE ROOM SHALL BE CIRCUITED AND CONTROLLED ALONG WITH THE LIGHTING FIXTURES IN THE SAME ROOM.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH MECHANICAL CONTRACTOR FOR EXACT LOCATION AND POWER REQUIREMENTS OF MECHANICAL EQUIPMENTS.
- E.C. SHALL COORDINATE WITH ARCHITECT/OWNER FOR EXACT LOCATION OF PANELS AND TRANSFORMER PRIOR TO ROUGH-IN.
- E.C. SHALL COORDINATE WITH UTILITY FOR EXACT LOCATION OF ELECTRICAL METER AND CT CABINET.
- E.C. SHALL COORDINATE WITH ARCHITECTURAL ELEVATIONS FOR EXACT LOCATION OF THE SIGNAGES.

POWER PLAN GENERAL NOTES:

- LOCATE DOUBLE DUPLEX (QUAD) RECEPTACLES ON WALL ABOVE EQUIPMENT. E.C. SHALL VERIFY EXACT LOCATIONS WITH OWNER PRIOR TO ROUGH-IN.
- ELECTRICAL WORK IN EQUIPMENT ROOM SHALL BE SURFACE MOUNT WITH EXPOSED CONDUIT.
- REFER TO EQUIPMENT DRAWINGS FOR WORK ASSOCIATED WITH FURNISHING AND INSTALLATION OF PROCESS EQUIPMENT AND MCC.

PANEL:	MDP	(NEW)					MOUNTING:		SURFACE					
277/480	VOLTS		3	PHASE	4	WIRE	PANEL LOCATION: MECHANICAL ROOM							
MCB	800A		BUS:	800A	MINIMUM		FED FROM: ELECTRICAL METER							
NOTE:														
CKT NO.	TRIP AMPS	DESCRIPTION OF LOAD	LOAD TYPE	LOAD (KVA)	MINIMUM BRANCH CIRCUIT	PER PHASE (KVA)			MINIMUM BRANCH CIRCUIT	LOAD (KVA)	LOAD TYPE	DESCRIPTION OF LOAD	TRIP AMPS	CKT NO.
						A	B	C						
1	30/3P	COMPRESSOR 10HP (S) STARTER	E	3.80	3#10, 1#10, 3/4"C	6.80			3#12, 1#12, 3/4"C	3.00	E	RECLAIM 7.5HP (D)	20/3P	2
3			E	3.80		6.80	6.80	3.00		E	4			
5			E	3.80			6.80	3.00		E	6			
7	30/3P	COMPRESSOR 10HP (S) STARTER	E	3.80	3#10, 1#10, 3/4"C	5.00			3#12, 1#12, 3/4"C	1.20	E	RO UNIT 3HP STARTER (I)	20/3P	8
9			E	3.80		5.00	5.00	1.20		E	10			
11			E	3.80			5.00	1.20		E	12			
13	20/3P	CHEM PUMP	E	3.00	3#12, 1#12, 3/4"C	4.00			3#12, 1#12, 3/4"C	1.00	E	RO PRESSURIZER 2HP(F) STARTER	20/3P	14
15			E	3.00			4.00	1.00		E	16			
17			E	3.00			4.00	1.00		E	18			
19	20/3P	RO JET PUMP 2HP STARTER	E	1.00	3#12, 1#12, 3/4"C	4.00			3#12, 1#12, 3/4"C	3.00	E	H2O REP. PUMP, HYDRAFLEX	20/3P	20
21			E	1.00			4.00	3.00		E	22			
23			E	1.00			4.00	3.00		E	24			
25	100/3P	VACUUM PUMP 40HP, VFD	M	13.81	3#3, 1#8, 2"C	31.07			3#1, 1#6, 2"C	17.26	M	VACUUM PUMP 50HP, VFD	125/3P	26
27			M	13.81			31.07	17.26		M	28			
29			M	13.81			31.07	17.26		M	30			
31	20/3P	SPARE				0.00						SPARE	20/3P	32
33							0.00				34			
35								0.00					36	
37	125/3P	75 KVA TRANSFORMER	O	14.56	3#1, 1#6, 1 1/4"C	110.56			2 X (4-350KCM, 1#1G, 3"C	96.00	O	TO MCC	600/3P	38
39			O	14.56			110.56	96.00		O	40			
41			O	14.56			110.56	96.00		O	42			
						161.43	161.43	161.43						

PANEL:	LV	(NEW)					MOUNTING:		SURFACE					
120/208	VOLTS		3	PHASE	4	WIRE	PANEL LOCATION: MECH. ROOM							
MCB	225		BUS:	225A	MINIMUM		FED FROM: TRANSFORMER							
NOTE:														
CKT NO.	TRIP AMPS	DESCRIPTION OF LOAD	LOAD TYPE	LOAD (KVA)	MINIMUM BRANCH CIRCUIT	PER PHASE (KVA)			MINIMUM BRANCH CIRCUIT	LOAD (KVA)	LOAD TYPE	DESCRIPTION OF LOAD	TRIP AMPS	CKT NO.
						A	B	C						
1	20	OFFICE, TOILET, WAITING LIGHTING	L	0.40	2#12, 1#12, 3/4"C	1.00			2#12, 1#12, 3/4"C	0.60	L	TUNNEL LIGHTING	20	2
3	20	EXTERIOR LIGHTING	L	0.60	2#12, 1#12, 3/4"C		1.20		2#12, 1#12, 3/4"C	0.60	L	SITE LIGHTING	20	4
5	20	SIGNAGE	L	1.00	2#12, 1#12, 3/4"C			1.00				SPARE	20	6
7	20	VACCUUM LIGHTING	L	1.00	2#10, 1#10, 1"C	1.80			2#12, 1#12, 3/4"C	0.80	L	MECHANICAL ROOM LIGHTING	20	8
9	20	VACCUUM LIGHTING	L	1.00	2#10, 1#10, 1"C		1.00					SPARE	20	10
11	20	SIGNAGE	L	1.00	2#12, 1#12, 3/4"C			1.60	2#12, 1#12, 3/4"C	0.60	R	EXT. BUILDING RECEPATCLE	20	12
13	20	MONSTER ARCH	R	0.90	2#12, 1#12, 3/4"C	2.40			2#12, 1#12, 3/4"C	1.50	O	WH-1	20	14
15	20	PAY STATION	R	1.00	2#10, 1#10, 1"C		2.50		2#12, 1#12, 3/4"C	1.50	O	WH-2	20	16
17	20	WAIT AND GO	R	0.30	2#12, 1#12, 3/4"C			0.70	2#12, 1#12, 3/4"C	0.40	R	CONTROL_120V	20	18
19	20	PAY STATION	R	1.00	2#10, 1#10, 1"C	1.00					R	SPARE	20	20
21	20	MASTER COMP.	R	0.60	2#12, 1#12, 3/4"C		1.00		2#12, 1#12, 3/4"C	0.40	R	CONTROL_120V	20	22
23	20	MAT BRUSHER	E	1.00	2#10, 1#10, 1"C			1.00			R	SPARE	20	24
25	20	RELAY BOX	R	0.40	2#12, 1#12, 3/4"C	0.80			2#12, 1#12, 3/4"C	0.40	R	CONTROL_120V	20	26
27	20	EQ ROOM RECEPTACLE	R	0.50	2#12, 1#12, 3/4"C		0.50				R	SPARE	20	28
29	20	RECEPTACLE OFFICE	R	0.90	2#12, 1#12, 3/4"C			1.30	2#12, 1#12, 3/4"C	0.40	R	CONTROL_120V	20	30
31	20/2P	RECEPTACLE WAITING	R	0.90	2#12, 1#12, 3/4"C	1.40			2#12, 1#12, 3/4"C	0.50	R	SOFTNER	20	32
33	20	MAINTENANCE RECEPATCLE	R	0.60	2#12, 1#12, 3/4"C		1.62		2#12, 1#12, 3/4"C	1.02	R	OVERHEAD DOORS	20/2P	34
35	20/2P	AHU-1 (N)	H	0.30	2#12, 1#12, 3/4"C			1.32		1.02	R		20/2P	36
37			H	0.30		1.10		0.80	E	AIR DRYER 1/3HP	20	38		
39	20	LED CARWASH EQ. LIGHT	L	0.90	2#12, 1#12, 3/4"C		1.40		2#12, 1#12, 3/4"C	0.50	H	UH-2(N)	20	40
41	20	LED CARWASH EQ. LIGHT	L	0.97	2#12, 1#12, 3/4"C			1.47	2#12, 1#12, 3/4"C	0.50	H	UH-1(N)	20	42
43	20	COMPUTER QUAD	R	0.90	2#12, 1#12, 3/4"C	1.50			2#12, 1#12, 3/4"C	0.60	E	GATE	20/2P	44
45	20/2P	CU-1(N)	H	1.20	2#12, 1#12, 3/4"C		1.80			0.60	E		20/2P	46
47			H	1.20			1.90		0.70	E	SIGN	20/2P	48	
49	20	RTH-1(N)	H	0.60	2#12, 1#12, 3/4"C	1.30			2#12, 1#12, 3/4"C	0.70	E		20/2P	50
51	20	RTH-2(N)	H	0.60	2#12, 1#12, 3/4"C		1.40		2#12, 1#12, 3/4"C	0.80	E	XPT	20/2P	52
53	20	B-1	H	0.60	2#12, 1#12, 3/4"C			1.40	2#12, 1#12, 3/4"C	0.80	E		20/2P	54
55	20	HAND DRYER	M	0.72	2#12, 1#12, 3/4"C	2.82				2.10	M		20/2P	56
57	20	12" X 48" SINGNAGES	L	0.10	2#12, 1#12, 3/4"C		2.20		3#8, 1#10, 3/4"C	2.10	M	BOOSTER PUMP	35/3P	58
59	20	SPARE						2.10		2.10	M		35/3P	60
						15.12	14.62	13.79						



- GENERAL NOTES:**
- A. ELECTRICAL CONTRACTOR TO COORDINATE FAULT CURRENT (isc) RATING WITH UTILITY COMPANY AND AHJ PRIOR TO BID.
- ELECTRICAL RISER SYMBOLS**
- NEW
 - EXISTING ITEM/FEEDER TO REMAIN
 - EXISTING ITEM/FEEDER TO BE DISCONNECTED & REMOVED
- 7 RISER DIAGRAM KEYED NOTES:**
- NEW 800 AMPS, 277/480V 3-PHASE INCOMING ELECTRICAL SERVICE FEEDER FROM UTILITY TRANSFORMER. E.C TO COORDINATE WITH UTILITY/OWNER FOR MORE DETAILS.
 - NEW 800 AMPS, 277/480V, 3-PHASE ELECTRICAL METER AND CT CABINET FOR THE SPACE. E.C. SHALL COORDINATE WITH UTILITY/OWNER FOR EXACT LOCATION OF ELECTRICAL METER AND CT CABINET.
 - SURGE PROTECTOR SPE-SQ D, MA-106KA-480Y/277V, 3P, 4W, T4X, SSP04MR16S OR EQUIVALENT, 4#6, 1#6G, 1"C
 - 800 AMPS, 277/480V, 3-PHASE, 4-WIRE NEW ELECTRICAL PANEL "MDP" E.C. SHALL CO-ORDINATE WITH ARCHITECT/OWNER FOR EXACT LOCATION OF PANEL.
 - 600 AMPS, 277/480V, 3-PHASE, 4-WIRE 60HZ MCC WITH 600 AMP BUS FOR SPACE. TO BE FURNISHED BY CAR WASH EQUIPMENT SUPPLIER. CONFIRM EQUIPMENT REQUIREMENT PRIOR TO BID.
 - 225 AMPS, 208/120V, 3-PHASE, 4-WIRE NEW ELECTRICAL PANEL "LV" E.C. SHALL CO-ORDINATE WITH ARCHITECT/OWNER FOR EXACT LOCATION OF PANEL.
 - 75KVA, 277/480V PRIMARY TO 120/208 SECONDARY, 3-PHASE NEW ELECTRICAL TRANSFORMER FOR SPACE. E.C. SHALL CO-ORDINATE WITH ARCHITECT/OWNER FOR EXACT LOCATION OF TRANSFORMER.

GO CAR WASH-INWOOD,
WV
 INWOOD-BERKELEY COUNTY, WV
ELECTRICAL SCHEDULES

PLUMBING SYMBOLS LIST

— OSAN —	OIL & SAND SANITARY SEWER (UNDERFLOOR)
— SAN —	SANITARY SEWER (UNDERFLOOR)
----	VENT PIPING
----	COLD WATER PIPING
----	EXISTING COLD WATER PIPING
— G —	GAS PIPING
—○—	P-TRAP
—○—	PIPE UP
—○—	PIPE DROP
—○—	CLEANOUT
—○—	PLUGGED OUTLET/CLEANOUT
—○—	POINT OF CONNECTION

PLUMBING ABBREVIATIONS

CO	CLEANOUT
CW	COLD WATER
HW	HOT WATER
HWR	HOT WATER RETURN
SW	WATER SOFTNER
SAN	SANITARY
V	VENT
LAV	LAVATORY
WC	WATER CLOSET
TYP.	TYPICAL
DN	DOWN
FD	FLOOR DRAIN
OI	SAND & OIL INTERSEPTOR
BFP	BACK FLOW PREVENTER
WH-1	WATER HEATER
N.I.C.	NOT IN CONTRACT

PLUMBING DRAWING LIST

- P1.1 PLUMBING SPECIFICATIONS
- P2.1 PLUMBING SANITARY PLAN
- P2.2 PLUMBING WATER AND GAS PLAN
- P3.1 PLUMBING DETAILS

BUILDING DEPARTMENT PLUMBING NOTES

1. ALL PLUMBING SYSTEMS (SANITARY, WASTE, VENT, WATER, STORM) AND ASSOCIATED EQUIPMENT SHALL BE INSTALLED, OPERATED AND MAINTAINED IN ACCORDANCE WITH THE REQUIREMENTS OF 2015 INTERNATIONAL PLUMBING CODE.
2. INSTALLATION OF UNDERGROUND PIPING SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 702.2
3. PROTECTION OF PIPING AND PLUMBING SYSTEM COMPONENTS AS PER SECTION PC 305.
4. TRENCHING, EXCAVATION AND BACKFILL AS PER SECTION PC 306.
5. RODENT PROOFING AS PER PC 304
6. MATERIALS USED IN PLUMBING SYSTEMS SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 303, PC 605, PC 702, PC 902, PC 1102.
7. EQUIPMENT CONNECTIONS AND JOINING OF PIPING SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTERS 4, 5, 6, 7 AND 9.
8. DEEP SEAL TRAPS FOR FLOOR DRAINS SHALL BE PROVIDED AS PER PC 1002, AND CLEAN-OUTS SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 708
9. DRAINAGE PIPE CLEANOUTS AS PER SECTION PC 708.
10. VERTICAL AND HORIZONTAL PIPING SHALL BE SUPPORTED IN ACCORDANCE WITH THE REQUIREMENTS OF SECTION PC 308
11. WATER SUPPLY SYSTEMS SHALL BE INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTER 6 SECTION PC 601-603, 604, 606, 607, 608, 610
12. THE SANITARY DRAINAGE SYSTEM SHALL BE SIZED AND INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTER 7 SECTION PC 701, 704, 705, 706, 707, 708, 711.
13. VENT PIPING FOR THE SANITARY DRAINAGE SYSTEM SHALL BE INSTALLED IN ACCORDANCE WITH THE REQUIREMENTS OF CHAPTER 9 SECTIONS PC 901 THROUGH PC 912 THROUGH PC 917
14. INSPECTION AND TESTING OF PLUMBING SYSTEMS SHALL BE IN ACCORDANCE WITH SECTION PC 107.
15. GAS PIPING INSTALLATION SHALL BE IN ACCORDANCE WITH INTERNATIONAL FUEL GAS CODE CHAPTER 4.

PLUMBING SPECIFICATIONS:

1. BASIC PLUMBING REQUIREMENTS, MATERIALS AND METHODS

- 1.01 SCOPE
- A. PROVIDE ALL MATERIAL, TOOLS, SUPERVISION AND LABOR INCLUDING ALL MISCELLANEOUS AND INCIDENTAL ITEMS REQUIRED FOR COMPLETE AND OPERABLE PLUMBING INSTALLATIONS AS SHOWN OR DESCRIBED ON THE DRAWINGS AND IN THESE SPECIFICATIONS.
 - B. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROTECTION OF ALL EXISTING AND NEW CONDITIONS AND MATERIALS WITHIN THE CONSTRUCTION AREA. ANY DAMAGE CAUSED BY THE CONTRACTOR SHALL BE REPAIRED TO THE OWNER'S SATISFACTION.
 - C. OBTAIN ALL PERMITS, PAY ALL PERMIT FEES AND SCHEDULE ALL REQUIRED INSPECTIONS. COPIES OF ALL PERMITS AND INSPECTION CERTIFICATES SHALL BE FORWARDED TO THE OWNER FOR RECORD.
 - D. THE GENERAL CONDITIONS OF THE CONTRACT AND ALL DIVISION 1 REQUIREMENTS APPLY TO THE WORK OF THIS SECTION.
 - E. THE CONTRACTOR SHALL VISIT THE SITE PRIOR TO SUBMITTING BID TO DETERMINE CONDITIONS AND THE EXTENT OF THE WORK. BY COMMENCING WORK, THE CONTRACTOR ACKNOWLEDGES HIS CONFIRMATION OF ALL CONDITIONS AS ACCEPTABLE WITH REFERENCE TO HIS CONTRACT, SCOPE OF WORK AND BID PRICE SUCH THAT NO ADDITIONAL COMPENSATION SHALL BE FORTHCOMING FOR UNFORESEEN EXISTING CONDITIONS.
 - F. IN ALL AREAS SUBJECT TO FREEZING CONDITIONS, THE CONTRACTOR SHALL PROVIDE FREEZE PROTECTION FOR ALL DOMESTIC WATER PIPING INSTALLED UNDER HIS CONTRACT.
 - G. ALL ELECTRICAL REQUIREMENTS SHALL BE COORDINATED WITH THE CONTRACTOR FOR ELECTRICAL WORK. THIS CONTRACTOR IS RESPONSIBLE FOR ALL LOW VOLTAGE WIRING FOR EQUIPMENT INSTALLED UNDER HIS CONTRACT. THE CONTRACTOR FOR ELECTRICAL WORK IS RESPONSIBLE FOR LINE VOLTAGE POWER WIRING ONLY.
 - H. COLOR AND FINISH SELECTIONS FOR ALL MATERIALS, INCLUDING PAINTING OF PIPING, SHALL BE AS DIRECTED AND/OR APPROVED BY THE ARCHITECT.
 - I. MINOR DETAILS NOT SHOWN OR SPECIFIED, BUT NECESSARY FOR THE PROPER AND ACCEPTABLE CONSTRUCTION, INSTALLATION OR OPERATION OF ANY PART OF THE WORK AS DETERMINED BY THE ENGINEER SHALL BE INCLUDED AS IF SPECIFIED OR INDICATED ON THE DRAWINGS.
 - J. THIS CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING ALL REQUIREMENTS FOR THE INSTALLATION, CONNECTION, EXTENSION OR MODIFICATION TO ALL UTILITY SERVICES WITH RESPECTIVE PROVIDERS INCLUDING PAYMENT OF ALL ASSOCIATED FEES.
 - K. THE CONTRACTOR IS RESPONSIBLE FOR ALL PAINTING ASSOCIATED WITH CUTTING AND PATCHING ALL PAINTING IN AREAS WITH COMPLETE FINISH RENOVATIONS SHALL BE PROVIDED BY THE GENERAL CONTRACTOR.

1.02 SUBMITTALS

- A. SUBMITTAL REQUIREMENTS SHALL BE COORDINATED WITH THE ARCHITECT AND AUTHORITIES HAVING JURISDICTION. UNLESS OTHERWISE DIRECTED, CONTRACTOR SHALL PROVIDE SUBMITTALS AS LISTED BELOW.
 1. PIPE AND FITTINGS
 2. VALVES
 3. HANGERS AND SUPPORTS
 4. PLUMBING PIPING LAYOUT
 5. TESTS
 6. PLUMBING FIXTURES
 7. WATER HEATERS & ACCESSORIES
 8. MIXING VALVES
 9. ALL SCHEDULED PLUMBING EQUIPMENT
- B. SUBMITTALS FROM SUPPLIERS OR MANUFACTURERS WHICH DO NOT BEAR THE STAMP OF THE SUBMITTING CONTRACTOR INDICATING THAT THE CONTRACTOR HAS REVIEWED THE SUBMITTAL FOR CONFORMANCE WITH THE PROJECT REQUIREMENTS WILL BE RETURNED REJECTED.
- C. THE ENGINEER'S REVIEW OF SUBMITTALS IS A COURTESY WHICH DOES NOT RELIEVE THE CONTRACTOR FROM CONFORMING WITH THE CONSTRUCTION DOCUMENTS, REGARDLESS OF THE ACTION INDICATED BY THE SHOP DRAWINGS STAMP.
- D. REVIEW OF SHOP DRAWINGS BY THE ENGINEER SHALL BE LIMITED TO THE INITIAL REVIEW, AND A SECOND REVIEW OF ANY REQUIRED RESUBMITTED DATA. IF THE ENGINEER IS REQUIRED TO REVIEW SHOP DRAWINGS FOR A THIRD (OR MORE) SUBMISSION OF THE SAME ITEM, THE CONTRACTOR SHALL BE LIABLE FOR COMPENSATING THE ENGINEER FOR THESE SUBSEQUENT REVIEWS AS PER THE ENGINEER'S CURRENT HOURLY RATE SCHEDULE.
- E. SUBMIT PROOF OF APPROVAL AND/OR CONFIRMATION OF SATISFACTORY TEST RESULTS TO THE OWNER AND THE ARCHITECT.
- F. SUBMIT TO THE OWNER'S MAINTENANCE PERSONNEL OPERATION AND MAINTENANCE DATA FOR ALL SYSTEM COMPONENTS, SERVICING REQUIREMENTS, INSPECTION DATA, REPLACEMENT PART NUMBERS AND AVAILABILITY AND CONTACT INFORMATION FOR SERVICE/SUPPLY COMPANY.
- G. FOR ALL BELOW GRADE PIPING WHERE ACTUAL INSTALLATION DEVIATES FROM CONSTRUCTION DRAWINGS, THE CONTRACTOR SHALL PROVIDE AS-BUILT DRAWINGS INDICATING BELOW GRADE PIPE LOCATIONS DIMENSIONED TO NEAREST COLUMN LINES.
- H. RECORD AS-BUILT DRAWINGS SHALL BE SUPPLIED TO THE OWNER/TENANT AFTER COMPLETION OF THE WORK SHOWING ANY ALTERATIONS, ADDITIONS AND/OR DELETIONS TO THE SYSTEM(S) INSTALLED.

1.03 SUBSTITUTIONS

- A. ALL EQUIPMENT SHALL BE PRODUCTS OF THE SPECIFIED MANUFACTURER OR MANUFACTURERS. ALL BIDS SHALL BE BASED ON THE SPECIFIED MANUFACTURER OR MANUFACTURER'S EQUIPMENT. FOR SUBSTITUTIONS OF OTHER MANUFACTURER'S EQUIPMENT TO BE CONSIDERED, THE SUBSTITUTION MUST BE INDICATED PRIOR TO BIDDING WITH THE REASON FOR THE PROPOSED SUBSTITUTION IDENTIFIED, AND THE PROPOSED CREDIT TO THE OWNER INDICATED, THE ENGINEER SHALL DETERMINE THE ACCEPTABILITY OF ANY PROPOSED SUBSTITUTIONS.
- B. THE CONTRACTOR ASSUMES ALL RESPONSIBILITY FOR COORDINATING THE WORK OF OTHER TRADES WHICH MAY BE AFFECTED BY SUBSTITUTIONS, INCLUDING ALL RELATED COSTS.

1.05 DEFINITIONS

- A. FURNISH: TO PURCHASE, PROCURE, ACQUIRE AND DELIVER, COMPLETE WITH RELATED ACCESSORIES.
- B. INSTALL: TO ERECT, MOUNT AND CONNECT, COMPLETE WITH RELATED ACCESSORIES.
- C. PROVIDE: TO FURNISH AND INSTALL.
- D. PLUMBING CONTRACTOR, THE CONTRACTOR, THIS CONTRACTOR: THE CONTRACTOR FOR PLUMBING WORK WHICH IS SPECIFIED HEREIN AND SHOWN ON THESE DRAWINGS.

1.06 DRAWINGS

- A. THE DRAWINGS ARE DIAGRAMMATIC AND ARE INTENDED TO ILLUSTRATE THE GENERAL ARRANGEMENT AND ROUTING OF PIPING AND GENERAL LOCATIONS OF EQUIPMENT. PRECISE LOCATIONS OF EQUIPMENT, RISERS AND STACKS, AND ROUTING AND ELEVATION OF ALL PIPING SYSTEMS SHALL BE COORDINATED IN THE FIELD WITH THE ARCHITECT, ARCHITECTURAL DRAWINGS, THE WORK OF OTHER TRADES, EXISTING AND NEW BUILDING CONDITIONS AND/OR THE PREFERENCES OF THE OWNER/TENANT AS CONSTRUCTION PROCEEDS. ALL PIPING SHALL BE INSTALLED CONCEALED IN FINISHED SPACES, UNLESS NOTED OTHERWISE.
- B. PROVIDE ALL NECESSARY INCIDENTAL MATERIALS AND ACCESSORIES REQUIRED TO MAKE THE WORK COMPLETE IN ALL RESPECTS, EVEN IF NOT PARTICULARLY SHOWN OR SPECIFIED.
- C. REFER TO PLUMBING EQUIPMENT/FIXTURE SCHEDULE ON THE DRAWINGS FOR ALL FIXTURE AND EQUIPMENT SPECIFICATIONS.
- D. REFER TO FIXTURE CONNECTION SIZE SCHEDULE FOR ALL FIXTURE ROUGHING SIZE REQUIREMENTS.
- E. VERIFY ALL INDICATED CONDITIONS BEFORE STARTING WORK AND REPORT ANY DISCREPANCIES. THE DRAWINGS REFLECT CONDITIONS WHICH CAN BE REASONABLY INTERPRETED FROM THE EXISTING VISIBLE CONDITIONS OR FROM DRAWINGS AND INFORMATION FURNISHED BY THE OWNER.
- F. LOCATE ALL FIXTURES AND EQUIPMENT AS PER THE FINAL ARCHITECTURAL DRAWINGS.

1.07 PRODUCTS

- A. SANITARY AND VENT PIPING:
1. SANITARY PIPING SHALL BE HUBLESS CAST IRON PIPE WITH STAINLESS STEEL COUPLINGS AND ELASTOMERIC GASKETS WITH A MINIMUM 4 BANDS PER COUPLING.
 2. SLOPE OF DRAINAGE SYSTEM SHALL BE 1/8" PER FOOT OF RUN FOR PIPE OVER 3" (I.D.) AND 1/4" PER FOOT OF RUN FOR PIPE 3" AND SMALLER (I.D.). VENT PIPING SHALL BE PITCHED TO DRAIN.
 3. ALL CAST IRON SOIL PIPE AND FITTINGS SHALL BE MARKED WITH THE COLLECTIVE TRADEMARK OF THE CAST IRON SOIL PIPE INSTITUTE (CISPI) AND BE LISTED BY NSF INTERNATIONAL.

B. DOMESTIC WATER PIPING:

1. ABOVE GRADE WATER PIPING SHALL BE TYPE 'L' HARD-DRAWN COPPER TUBE.
2. FITTINGS IN DOMESTIC WATER PIPING SHALL BE WROUGHT COPPER OR CAST BRASS.
3. JOINTS SHALL BE MADE WITH LEAD-FREE SOLDER.
4. THE ENTIRE DOMESTIC WATER DISTRIBUTION SYSTEM SHALL BE INSULATED INCLUDING ALL VALVES, FITTINGS, ETC.
5. COMPLY WITH NSF 61 FOR MATERIALS FOR WATER-SERVICE PIPING AND SPECIALTIES FOR DOMESTIC WATER.
6. AS PER ASHRAE-90.1 2010 ENERGY CODE C7.4.4.1, TEMPERATURE CONTROLS SHALL BE PROVIDED THAT ALLOW FOR STORAGE TEMPERATURE ADJUSTMENT FROM 120°F OR LOWER TO A MAXIMUM TEMPERATURE COMPATIBLE WITH THE INTENDED USE.
7. AS PER ASHRAE-90.1 2010 ENERGY CODE C7.4.6, STORAGE WATER HEATERS AND STORAGE TANKS NOT HAVING INTEGRAL HEAT TRAPS AND SERVING A NON RE-CIRCULATING SYSTEM SHALL HAVE HEAT TRAPS ON BOTH THE INLET AND OUTLET PIPING AS CLOSE AS PRACTICAL TO THE STORAGE TANK.
8. AS PER ASHRAE-90.1 2010 ENERGY CODE C7.4.4.3, TEMPERATURE CONTROLLING MEANS SHALL BE PROVIDED TO LIMIT THE MAXIMUM TEMPERATURE OF WATER DELIVERED FROM LAVATORY FAUCETS IN PUBLIC FACILITY RESTROOMS TO 110°F.
9. AS PER ASHRAE-90.1 2010 ENERGY CODE C7.4.3, THE FIRST 8 FT OF OUTLET PIPING FOR A CONSTANT TEMPERATURE NON RE-CIRCULATING STORAGE SYSTEM

C. HANGERS AND SUPPORTS:

1. HANGERS SHALL BE STANDARD STEEL, MALLEABLE OR WROUGHT IRON, AS MANUFACTURED BY GRINNELL OR APPROVED EQUAL, SUITABLE FOR THE TYPE OF CONSTRUCTION. PIPING SHALL NOT BE HUNG FROM OTHER PIPE.
2. SECTIONS OF INDIVIDUAL PIPE RUNS SHALL BE SUPPORTED BY CLEVIS HANGERS.
3. ALL EQUIPMENT SHALL BE PROVIDED WITH APPROVED SUPPORTS.
4. PROVIDE SEISMIC RESTRAINTS IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL CODES AND STANDARDS AND THE REQUIREMENTS OF AUTHORITIES HAVING JURISDICTION.
5. SUPPORTS SHALL BE PROVIDED IN STRICT ACCORDANCE WITH THE RECOMMENDATIONS OF THE PIPING MANUFACTURER.

D. VALVES:

1. PROVIDE GATE VALVES, BUTTERFLY OR BALL VALVES FOR SHUT-OFF DUTY ON MAIN AND BRANCH SUPPLY LINES. FOR ALL PIPE RUNS 2" AND SMALLER, PROVIDE BALL FOR ALL PIPE RUNS LARGER THAN 2" AND SMALLER THAN 4", PROVIDE GATE VALVES. PIPING 4" AND LARGER, PROVIDE BUTTERFLY VALVES FOR SHUT-OFF DUTY.
2. ALL FIXTURES WITH THE EXCEPTION OF FLUSHMETER-EQUIPPED WATER CLOSETS AND URINALS SHALL HAVE STOP VALVES TO CONTROL SUPPLY TO THE FIXTURE. WHERE SUPPLIES ARE EXPOSED PROVIDE CHROME-PLATED STOPS WITH CHROME-PLATED ESCUTCHEONS ON PIPING PENETRATIONS.
3. ALL PLUMBING FIXTURES AND EQUIPMENT TO HAVE SHUT-OFF VALVES ON SUPPLY LINES.
4. ALL BRANCH LINES TO HAVE SHUT-OFF VALVES.
5. ALL VALVES SHALL BE ACCESSIBLE. PROVIDE ACCESS DOORS WHERE REQUIRED FOR VALVE ACCESS.
6. PROVIDE GLOBE VALVES FOR THROTTLING/BALANCING OF THE HOT WATER CIRCULATING SYSTEM.

E. GAS PIPING:

1. GAS PIPING SHALL BE SIZED IN ACCORDANCE WITH PIPE SIZING TABLES OR SIZING EQUATIONS IN ACCORDANCE WITH 2015 INTERNATIONAL FUEL GAS CODE SECTION 402.4.
2. INDIVIDUAL OUTLETS TO GAS RANGES SHALL NOT BE LESS THAN 3/4 INCHES NPS.
3. METALLIC PIPE SHALL COMPLY WITH SECTIONS 403.4.1 THROUGH 403.4.4.
4. PIPING SYSTEM INSTALLATION SHALL COMPLY WITH REQUIREMENTS OF 2015 INTERNATIONAL FUEL GAS CODE SECTION 404.
5. AS PER 2015 INTERNATIONAL FUEL GAS CODE SECTION 404.4; UNDERGROUND PIPING, WHERE INSTALLED BELOW GRADE THROUGH THE OUTER FOUNDATION OR BASEMENT WALL OF A BUILDING, SHALL BE ENCASED IN A PROTECTIVE PIPE SLEEVE. THE ANNULAR SPACE BETWEEN THE GAS PIPING AND THE SLEEVE SHALL BE SEALED.
6. PIPING INSTALLED UNDERGROUND BENEATH BUILDINGS IS PROHIBITED EXCEPT WHERE THE PIPING IS ENCASED IN A CONDUIT OF WROUGHT IRON OR STEEL PIPE DESIGNED TO WITHSTAND THE SUPERIMPOSED LOADS. THE CONDUIT SHALL BE PROTECTED FROM CORROSION IN ACCORDANCE WITH SECTION 404.11 AND SHALL BE INSTALLED IN ACCORDANCE WITH SECTION 404.11.1 OR 404.11.2 OF INTERNATIONAL FUEL GAS CODE.
7. AS PER INTERNATIONAL FUEL GAS CODE 2015 SECTION 404.12; UNDERGROUND PIPING SYSTEMS SHALL BE INSTALLED A MINIMUM DEPTH OF 12 INCHES BELOW GRADE.
8. THE GAS PIPING IS ENCASED IN A CONDUIT OF WROUGHT IRON OR STEEL PIPE TO WITH STAND THE SUPERIMPOSED LOADS.
9. SHUTOFF VALVES SHALL BE LOCATED IN PLACES SO AS TO PROVIDE ACCESS FOR OPERATION AND SHALL BE INSTALLED SO AS TO BE PROTECTED FROM DAMAGE.
- F. INSTALL PIPING TO CONSERVE BUILDING SPACE. DO NOT INTERFERE WITH USE OF BUILDING SPACE AND THE WORK OF OTHER TRADES. ALL PIPING RUN IN CEILING SHALL BE INSTALLED TIGHT TO THE STRUCTURE ABOVE.
- G. INSTALL PIPING TO ALLOW FOR EXPANSION AND CONTRACTION WITHOUT STRESSING PIPE, JOINTS OR CONNECTED EQUIPMENT. PROVIDE PIPE ANCHORS, GUIDES AND EXPANSION JOINTS OR LOOPS IN ALL HOT WATER AND HOT WATER CIRCULATING MAIN SUPPLY PIPING AND SEGMENTS OF SUCH PIPE THAT EXCEED 30'-0" IN LENGTH.
- H. IN ALL AREAS WITH FINISHED SURFACES, SYSTEM PIPING AND COMPONENTS SHALL BE CONCEALED ABOVE OR WITHIN FINISHED SURFACES.

- I. REDUCTIONS IN PIPE SIZES SHALL BE MADE WITH ONE-PIECE REDUCING FITTINGS. BUSHINGS ARE NOT ACCEPTABLE. USE FLANGED FITTINGS AT THE BASE OF RISERS.

J. VENT PENETRATIONS THROUGH THE ROOF SHALL BE FLASHED.

- K. IF WATER PRESSURE EXCEEDS 80 PSI, A WATER PRESSURE REDUCING VALVE SHALL BE INSTALLED IN WATER PIPING AT CONNECTION TO MAIN.
- L. PROVIDE DIELECTRIC FITTINGS BETWEEN DISSIMILAR METALS.
- M. PIPE BACKFLOW PREVENTER DRAINS TO FLOOR DRAIN OR OTHER APPROVED INDIRECT WASTE SOURCE.
- N. PROVIDE ACCESS DOORS/PANELS FOR SERVICE AND ACCESS TO ALL VALVES AND OTHER SYSTEM COMPONENTS ENCLOSED IN WALLS AND CEILINGS. ACCESS DOORS SHALL BE FURNISHED BY THIS CONTRACTOR, INSTALLED BY THE GENERAL CONTRACTOR.
- O. ALL FIXTURES REQUIRING VACUUM BREAKERS SHALL BE EQUIPPED WITH INTEGRAL VACUUM BREAKERS.
- P. ANY PENETRATIONS THROUGH FIRE RATED PARTITIONS, FLOORS, OR CEILINGS SHALL BE STEEL SLEEVED AND SEALED WITH 3M BRAND UL RATED FIRE BARRIER CAULK OR APPROVED EQUAL.
- Q. WHEN THE WATER PIPING SYSTEM IS COMPLETE, THOROUGHLY FLUSH ALL DIRT, SEDIMENT, SOLDER, ETC., OUT OF THE SYSTEM, REMOVING ALL STRAINERS, VALVE STEM SEATS, ETC., REQUIRED TO ACCOMPLISH THE FLUSHING.

- AT ALL INDIRECT WASTE DRAINS, MAINTAIN AIR GAP AS REQUIRED BY CODE.
- R. INSTALL SLEEVES FOR ALL PIPES WHICH PASS THROUGH WALLS, FLOORS, AND CEILINGS. WHERE PIPES ARE TO BE INSULATED, THE SLEEVE SHALL BE LARGE ENOUGH TO ACCOMMODATE INSULATION. SLEEVES SHALL BE FLUSH WITH FINISHED SURFACES AT BOTH ENDS. ON FINISHED SURFACES IN EXPOSED AREAS PROVIDE ESCUTCHEONS COMPATIBLE WITH FINISH.

2. INSTALLATION

2.01 GENERAL

- S. ALL WORK WHICH REQUIRES DISRUPTION OF THE ROOFING SHALL BE DONE BY A CONTRACTOR CERTIFIED BY THE ROOFING MANUFACTURER AS REQUIRED TO MAINTAIN ANY EXISTING ROOF WARRANTIES.
- T. EXTERIOR INSTALLATIONS TO BE WEATHER PROOF IN ALL RESPECTS.
- U. EXTERIOR MATERIALS AND EQUIPMENT SHALL BE PAINTED TO PREVENT CORROSION, COLOR PER ARCHITECT.
- V. COORDINATE THE PLUMBING WORK WITH ALL OTHER AFFECTED WORK AND THE CONSTRUCTION SCHEDULE.
- W. REAM PIPE AND TUBE ENDS. REMOVE BURRS. BEVEL PLAIN AND FERROUS END PIPE.
- X. REMOVE SCALE AND FOREIGN MATERIAL, FROM INSIDE AND OUTSIDE, BEFORE ASSEMBLY.
- Y. PREPARE PIPING CONNECTIONS TO EQUIPMENT WITH FLANGES AND UNIONS.
- Z. COORDINATION WITH THE WORK OF OTHER TRADES IS REQUIRED. PROVIDE OFFSETS IN PIPING SYSTEMS OR MINOR DEVIATIONS TO THE INDICATED PIPE ROUTING IN ORDER TO COORDINATE THE PLUMBING WORK WITH THE WORK OF ALL OTHER TRADES AND THE GENERAL BUILDING CONDITIONS.
- AA. NO DOMESTIC WATER PIPING SHALL BE INSTALLED IN UNHEATED SPACES.
- AB. PRIOR TO DISCONNECTING AND CONNECTING NEW WORK TO EXISTING SYSTEMS, THE PLUMBING CONTRACTOR SHALL NOTIFY THE PROPERTY MANAGER AND OFFER A PROPOSED SCHEDULE OF WORK. ESB WILL AUTHORIZE CONNECTIONS AND COORDINATE NECESSARY SHUT DOWNS AND DRAIN DOWNS AS REQUIRED. SHUT DOWNS AND DRAIN DOWNS MAY BE PERFORMED BY THE PLUMBING CONTRACTOR ONLY AFTER RECEIVING ESB AUTHORIZATION, AND SHOULD BE PERFORMED UNDER SUPERVISION OF ESB PERSONNEL. THREE (3) DAYS ADVANCE NOTICE TO THE PROPERTY MANAGER IS REQUIRED.
- AC. THE PLUMBING CONTRACTOR IS ADVISED THAT DUE TO THE NATURE OF THE OPERATIONS AND TENANT REQUIREMENTS, CONNECTIONS TO EXISTING SYSTEMS MAY HAVE TO BE MADE AFTER REGULAR WORKING HOURS. THE PROPERTY MANAGER WILL ADVISE THE PLUMBING CONTRACTOR OF THE TIME CONSTRAINTS UPON RECEIPT AND APPROVAL OF THE PLUMBING CONTRACTOR'S REQUEST FOR SHUT DOWN AND CONNECTION TO EXISTING SYSTEMS.
- AD. WHEN CONNECTING TO EXISTING STACKS AND RISERS, PROVISION IS TO BE MADE FOR FUTURE CONNECTIONS BY PROVIDING CAPPED AND VALVED OUTLETS ON DOMESTIC WATER RISERS AND PLUGGED OUTLETS ON THE SANITARY AND VENT STACKS.

2.02 ABOVE GRADE

- A. INSTALL PLUMBING PIPING IN ACCORDANCE WITH RECOGNIZED INDUSTRY PRACTICES TO ENSURE THAT PIPING COMPLIES WITH REQUIREMENTS AND SERVES INTENDED PURPOSES.
- B. ROUTE PIPING IN AN ORDERLY MANNER, PLUMB AND PARALLEL TO BUILDING STRUCTURE. MAINTAIN GRADIENT; SLOPE PIPING AND ARRANGE SYSTEMS TO DRAIN IN DOMESTIC WATER SYSTEMS. PROVIDE DRAIN VALVES AT MAIN SHUT-OFF VALVES AND ALL LOW POINTS IN PIPING.
- C. USE EXISTING CONNECTIONS AT MAINS WHERE AVAILABLE FOR NEW BRANCH PIPING. LOCATE ALL RISERS AND PIPING BEFORE CONSTRUCTION COMMENCES AND TAKE CARE NOT TO DAMAGE SAME. ANY DAMAGE OCCURRING TO THE EXISTING PIPING WILL BE THE SOLE RESPONSIBILITY OF THE CONTRACTOR.

3. TESTING

- A. AT THE COMPLETION OF THE PLUMBING WORK, COMPLETELY TEST THE ENTIRE INSTALLATION OF ALL SYSTEMS FOR PROPER OPERATION AND COMPLIANCE WITH APPLICABLE CODES AND LOCAL REQUIREMENTS. CORRECT ALL DEFICIENCIES FOUND.
- B. TESTING OF THE INSTALLED SYSTEMS SHALL BE MADE BY THE CONTRACTOR IN THE PRESENCE OF A REPRESENTATIVE OF THE OWNER.
- C. THE CONTRACTOR SHALL NOT COVER UP OR PERMANENTLY CONCEAL PIPING, DEVICES OR ANY PORTION OF NEWLY CONSTRUCTED PLUMBING SYSTEM(S) UNLESS SUCH SYSTEM, OR PORTION OF THE SYSTEM, HAS BEEN TESTED IN THE PRESENCE OF A REPRESENTATIVE OF THE OWNER AND INSPECTED BY THE LOCAL INSPECTOR AND APPROVED IN WRITING, EXCEPT PIPING PASSING THROUGH FLOORS, WALLS, PARTITIONS, OR BEAMS, FOR DISTANCES EQUAL TO THE THICKNESS OF SUCH FLOOR, WALL, PARTITION OR BEAM.
- D. THIS CONTRACTOR SHALL NOTIFY THE VARIOUS DEPARTMENTS, BUREAUS AND INDIVIDUALS AT LEAST TWO WEEKS IN ADVANCE OF THE TIME THAT THE TESTS ARE TO BE CONDUCTED.
- E. ALL DEFECTIVE PARTS SHALL BE REPLACED OR CORRECTED BY THIS CONTRACTOR AND AN EXTRA TEST OR TESTS SHALL BE MADE UNTIL THE OPERATION IS SATISFACTORY. ALL ARRANGEMENTS AND EXPENSES NECESSARY TO CONDUCT ALL TESTS REQUIRED BY THESE SPECIFICATIONS AND THE VARIOUS AGENCIES HAVING JURISDICTION OVER THE WORK INSTALLED UNDER THIS CONTRACT SHALL BE MADE BY THIS CONTRACTOR. NO EXTRA COMPENSATION WILL BE ALLOWED FOR THESE TESTS, THE COST THEREOF BEING INCLUDED IN THE LUMP SUM BID FOR THIS CONTRACT.
- F. WHERE ANY EVIDENCE OF STOPPAGE IS FOUND IN PIPING OR EQUIPMENT, THIS CONTRACTOR SHALL DISCONNECT, CLEAN, REPAIR AND RECONNECT ALL OBSTRUCTED PIPING OR EQUIPMENT AND SHALL ALSO PAY FOR ALL NECESSARY CUTTING AND REPAIRS TO ADJOINING WORK.
- G. ALL PIPING AND EQUIPMENT SHALL BE THOROUGHLY CLEANED INSIDE AND OUT, OF DIRT, CUTTINGS, OILS AND OTHER FOREIGN SUBSTANCES AND SHALL BE LEFT CLEAN.
- H. ALL REQUIRED TESTS SHALL BE WITNESSED BY LOCAL AUTHORITIES AND THE OWNER'S REPRESENTATIVE.
- J. ALL EQUIPMENT WILL BE FACTORY TESTED.
- I. CONTRACTOR SHALL IDENTIFY TO THE OWNER'S REPRESENTATIVE ANY LEAKS OR DAMAGE THAT OCCURS AS A RESULT OF SYSTEM TESTING. CONTRACTOR SHALL TAKE NECESSARY PRECAUTIONS TO LIMIT ANY POTENTIAL DAMAGE. CORRECTIVE ACTION REQUIRED AS A RESULT OF TESTING SHALL BE PERFORMED IMMEDIATELY AND AT THE CONTRACTOR'S EXPENSE.
- K. REPORT IN WRITING TO AUTHORITIES HAVING JURISDICTION, THE ARCHITECT AND THE OWNER THE RESULTS OF ALL TESTING.
- L. TESTING REQUIREMENTS
 - a. TEST ALL DOMESTIC WATER PIPING HYDROSTATICALLY TO 125 PSIG.
 - b. HYDROSTATIC TEST PRESSURES SHALL REMAIN CONSTANT WITH NO VARIATION FOR 120 MINUTES.
 - c. TESTS SHALL BE WITNESSED BY THE BUILDING ENGINEER.
 - d. THE PLUMBING CONTRACTOR WILL BE HELD RESPONSIBLE FOR ALL DAMAGE DUE TO TEST FAILURES AND LEAKAGE IN THE TEST AREA AND ADJACENT TENANT OR ESB SPACES.
- M. REFILL ENTIRE POTABLE HOT AND COLD WATER SUPPLY SYSTEM WITH CHLORINE SOLUTION (HTH OLIU CHEMICAL CORP.) AT A STRENGTH TO MEET STANDARDS OF THE DEPARTMENT OF HEALTH, AND FOR A PERIOD OF RETENTION AS STIPULATED.
- N. THOROUGHLY FLUSH PIPING SYSTEM WITH FRESH WATER IMMEDIATELY PRIOR TO FINAL ACCEPTANCE.


4. WARRANTY

- A. EQUIPMENT, MATERIALS AND WORKMANSHIP FURNISHED UNDER THIS CONTRACT SHALL BE GUARANTEED BY THE CONTRACTOR FOR A PERIOD OF ONE YEAR FROM THE DATE OF FINAL ACCEPTANCE OF THE WORK BY THE OWNER. THE CONTRACTOR SHALL KEEP THE WORK IN GOOD REPAIR FOR ONE YEAR AFTER THE DATE OF FINAL APPROVAL. THE CONTRACTOR SHALL, AT HIS OWN EXPENSE, PROMPTLY CORRECT AND REPAIR ANY AND ALL BREAKS, FAILURES OR WEAR DUE TO FAULTY MATERIALS, WORKMANSHIP OR EQUIPMENT. ALL SETTLEMENTS OF SURFACES THAT MAY OCCUR WITHIN THAT PERIOD SHALL ALSO BE PROMPTLY REPAIRED.

GO CAR WASH-INWOOD, WV
INWOOD-BERKELEY COUNTY, WV
PLUMBING SPECIFICATION

Sheet Number

P1.1



PLUMBING SANITARY PLAN
1
P2.1
1/8\"/>


GENERAL NOTES:

1. CONTRACTOR TO FIELD VERIFY FEASIBILITY OF SUB PENETRATION AS PER STRUCTURAL REQUIREMENT.
2. REFER RISER DIAGRAMS FOR ALL PIPE SIZES.


SANITARY PIPING PLAN NOTES:

1. CONNECT NEW 4\"/>

THE CAR WASH EQUIPMENT, SYSTEM DESIGN AND SPECIFICATIONS ARE BY THE CAR WASH EQUIPMENT VENDOR. GENERAL CONTRACTOR MUST COORDINATE ALL PLUMBING REQUIREMENTS WITH CAR WASH EQUIPMENT VENDOR INCLUDING CAR WASH VENDOR SPECIFICATIONS, PLANS AND DETAIL DRAWINGS. THESE PLANS DO NOT INCLUDE DETAILED PIPING DIAGRAMS FOR THE RECLAIM SYSTEM PIPING, WASH SYSTEM UNDERGROUND PIPING, CAR WASH EQUIPMENT ROOM SYSTEMS PIPING, TUNNEL SYSTEMS PIPING, OR RECLAIM SYSTEMS TANK FINAL LOCATIONS. REFER TO CAR WASH EQUIPMENT VENDORS PLANS AND SPECIFICATIONS FOR COMPLETE AND DETAILED INFORMATION.




2 SANITARY RISER DIAGRAM
P2.1
N.T.S.



- GENERAL NOTES:**
- CW/HW PIPING TO BE PROVIDED WITH INSULATION AS PER IECC 2015 (REFER SHEET P1.1)
 - PROVIDE BRANCH PRV IF PRESSURE EXCEEDS 80 PSI.
 - CONTRACTOR TO FIELD VERIFY FEASIBILITY OF SLAB PENETRATION AS PER STRUCTURAL REQUIREMENT.
 - PROVIDE ACCESS PANELS FOR WATER HAMMER ARRESTOR, CLEANOUTS & SHUT-OFF VALVES AS REQUIRED.
 - REFER RISER DIAGRAMS FOR ALL PIPE SIZES.
 - PROVIDE STAINLESS STEEL HYDRAULIC TUBING FOR OIL AND HIGH PRESSURE WATER PIPING BETWEEN EQUIPMENT IN EQUIPMENT ROOM AND TRANSITION TO FLEXIBLE HOSE AT EQUIPMENT IN CAR WASH TUNNEL. REFER TO MECHANICAL DRAWINGS FOR ADDITIONAL INFORMATION ON OIL AND HP WATER PIPING.
 - WORK SHALL COMPLY WITH VIRGINIA UNIFORM STATEWIDE BUILDING CODE

- WATER SUPPLY AND GAS PLAN NOTES:**
- CONNECT NEW 2" DOMESTIC WATER LINE TO EXISTING WATER LINE WITH NEW BFP AND WATER METER. CONTRACTOR TO FIELD VERIFY LOCATION AND SIZE.
 - CONTRACTOR TO FIELD VERIFY EXISTING AVAILABLE GAS PRESSURE AND MAKE SURE TO PROVIDE ADEQUATE INLET PRESSURE REQUIRED FOR MECHANICAL EQUIPMENT. CONTRACTOR TO VERIFY FINAL GAS METER LOCATION, SIZE AND PRESSURE WITH UTILITY COMPANY.

CONNECT NEW 2" CW LINE TO EXISTING WATER SUPPLY LINE (REFER CIVIL PLAN FOR CONTINUATION)




NAT. GAS DESIGN
LOW PRESSURE SYSTEM
INLET PRESSURE < 2.0PSI
PRESSURE DROP - 0.5 IN W.C.
LONGEST LENGTH - APPROX. 208'

GAS LOAD SUMMARY

EQUIPMENT TAG	CFH LOAD
UH-1(N)	60
UH-2(N)	60
RTH-1(N)	125
RTH-2(N)	125
B-1(N)	155
TOTAL LOAD	525

GAS PIPE SIZING BASED ON TABLE 402.4(2) 2015 INTERNATIONAL FUEL GAS CODE.

CONTRACTOR TO VERIFY EXACT TOTAL DEVELOPED LENGTH AND GAS SUPPLY PRESSURE IN FIELD AND NOTIFY ENGINEER IF DIFFERENT THAN SHOWN ON THIS PLAN



PLUMBING FIXTURE SCHEDULE

TAG	QTY	FIXTURE	SAN		VENT	CW	HW	REMARKS
			DIRECT	INDIRECT				
WC	1	WATER CLOSET	4"	-	2"	3/4"	-	①
LAV	1	LAVATORY	2"	-	1-1/2"	1/2"	1/2"	②
MS	1	MOP SINK	3"	-	2"	1/2"	1/2"	④
FD	6	FLOOR DRAIN	3"	-	2"	-	-	⑤
EW	1	EMERGENCY EYE WASH	2"	-	1-1/2"	1/2"	1/2"	③



- WATER CLOSET SHALL BE KOHLER K-3493-SS WITH BEMIS 1955C SETA OR ZURN Z5551 WITH Z5957 SEAT OR EQUAL. WATER CLOSET SHALL BE FLOOR MOUNTED, 2010 ADA COMPLIANT AND INCLUDE A PRESSURE ASSIST OPERATING SYSTEM. COLOR SHALL BE WHITE.
- LAVATORY SHALL BE KOHLER 2007 OR ZURN 5830 OR EQUAL. FAUCET SHALL BE KOHLER K-97828-4 OR ZURN Z7440-XL OR EQUAL. LAVATORY SHALL BE WALL MOUNTED AND WHITE, MOUNTED 34" AFF WITH A 29" CLEARANCE AFF TO BOTTOM OF LAVATORY APRON. PROVIDE PIPING UNDER SINK WITH TRAP-WRAP KIT FOR ADA COMPLIANCE. PROVIDE WITH WATER TEMPERATURE LIMITING DEVICE CONFORMING TO ASSE 1070. COLOR SHALL BE WHITE.
- EMERGENCY EYEWASH SHALL BE BRADLEY EYE-FACE WASH STATION MODEL S19224 WITH BRADLEY S19-2000 THERMOSTATIC MIXING VALVE. MOUNT 33"-45" AFF AND A MINIMUM 6" FROM ANY WALL OR OBSTRUCTION.
- MOP SINK EQUAL TO FIAT FL-1 WITH DECK TYPE FAUCET MODEL A-1.
- PROVIDE WITH TRAP PRIMER.

ELECTRIC POINT OF USE WATER HEATER

TAG NO	MANUFACTURER	MODEL	CAPACITY	KW	NO OF ELEMENT	V/PH/Hz	GPH RISE	REMARKS
WH-1	A.O SMITH	E6-12C15SV	12 GALLON	1.5	1	120/1/60	7 GPH @ 90°F	POINT OF USE STORAGE TYPE WATER HEATER - TYPICAL SIZE - 16" DIA X 22.75" HEIGHT
WH-2	A.O SMITH	E6-12C15SV	12 GALLON	1.5	1	120/1/60	7 GPH @ 90°F	

EXPANSION TANK SCHEDULE


TAG NO	SYSTEM	MANUFACTURER	MODEL	CAPACITY	SIZE AND REMARKS
ET-1	WH-1 & 2	AMTROL	ST-2	2 GALLON	MAXIMUM PRESSURE - 150 PSI SIZE - 8" DIA X 13" HEIGHT



PIPE SLEEVE VIEW

NOTES:




- FIRESTOP MATERIAL WRAP STRIP SHALL BE 1/2" THICK INTUMESCENT ELASTOMERIC MATERIAL FACED ON ONE SIDE WITH ALUMINUM FOIL SUPPLIED IN 2 IN. WIDE STRIPS AND WRAP AROUND THE PIPE AS PER UL MATERIAL LISTED 3M COMPANY FS-195+ OR FILL CAVITY WITH CAULK OR SEALANT MIN. 1/4" DIA. CONTINUOUS BEAD APPLIED TO THE WRAP STRIP/WALL INTERFACE AND TO THE EXPOSED OF THE WRAP STRIP LAYER APPROX. 3/4" FROM WALL SURFACE. AS PER UL LISTED 3M COMPANY GP25WB+, IC 15WB+, FIRE DAM 150+CAULK.
- PIPE COVERING INSULATION SHALL BE 2" THICK HOLLOW CYLINDRICAL HEAVY DENSITY GLASS FIBER UNITS JACKETED ON THE OUTSIDE WITH AN ALL SERVICE JACKETED, AS PER UL CLASSIFICATION AND MARKING WITH A FLAME SPREAD INDEX OF 25 OR LESS AND A SMOKE DEVELOPED INDEX OF 50 OR LESS MAY BE USED.



1 PIPE SLEEVE THRU WALL SECTION
P3.1 N.T.S.

2 WALL CLEANOUT DETAILS
P3.1 N.T.S.

3 WATER HEATER DETAILS
P3.1 N.T.S.



4 INSULATION OF PIPING, VALVES AND FITTINGS FOR EXPOSED AND CONCEALED LOCATIONS
P3.1 N.T.S.

5 HANGER DETAIL
P3.1 N.T.S.

6 FLOOR DRAIN DETAIL
P3.1 N.T.S.